

AIR IMPACT WRENCHES



## POWER TOOLS AIR IMPACT WRENCHES





**COMPACT MAGNESIUM HOUSING** 

6.4"/162mm from anvil to rear in total length



TRIGGER ACTIVATED LED LIGHTING

Powerful removable dual LED ring illuminates work areas with minimal shadowing

#### HIGH PERFORMANCE BREAKAWAY TORQUE

1,898 Nm breakaway torque



#### FORWARD HANDLE DESIGN

Forward design with rubber over-mould delivers balance, control, and comfort



#### PROPRIETARY FORGED ANVIL

Improved anvil life through new manufacturing process and materials



#### INNOVATIVE VALVE DESIGN

Innovative valve-lever designed for easy speed adjustment. Back cap grease fitting for ease of maintenance.

PRODUCT #	BREAKAWAY TORQUE Ft. LBS. / NM	AIR Consumption CFM	IMPACTS PER Minute FWD / Rev	FREE SPEED RPMS Rev/frw 3/frw 2/frw 1	DESIRED AIR Pressure PSI	SOUND LEVEL DB[A]	VIBRATION Level M/S2	WEIGHT LBS. / KG.	LENGTH IN. / MM.
MPF990501-XJ	1,400 / 1,898	5.9	1,100 / 1,200	6,500 / 5,500 / 4,500 / 2,200	90	94	6.4	4.8 / 2.2	6.4 / 162

## AIR IMPACT WRENCHES

**AWP075** 

3/4" DRIVE TITANIUM AIR IMPACT WRENCH

· Ergonomic handle is insulated

Hog-Ring anvil makes for quick and easy changing of sockets

for optimal speed control



MPF980501 1/2" DRIVE AIR **IMPACT WRENCH** 

- · Proprietary anvil forging process for long anvil life Variable-speed trigger for speed control
- Compact magnesium housing provides lightweight durability
- · Innovative valve-lever design for easy speed adjustment
- Forward handle design for comfort and balance
- Muffler pad designed to provide noise reduction



MPF980381 3/8" DRIVE AIR **IMPACT WRENCH** 

PRODUCT#	BREAKAWAY TORQUE FT. LBS. / NM	AIR Consumption CFM	IMPACTS PER Minute FWD / Rev	FREE SPEED RPMS REV / FRW 3 / FRW 2 / FRW 1	DESIRED AIR Pressure PSI	SOUND LEVEL DB[A]	VIBRATION Level M/S2	WEIGHT LBS. / KG.	LENGTH IN. / MM.	
MPF980381-XJ	575 / 780	6.1	1,300 / 1,400	12,000 / 10,000 / 9,000 / 4,000	90	95	5.5	2.8 / 1.3	5.6 / 143	
MPF980501-XJ	1,180 / 1,600	6.1	1,200 / 1,300	7,000 / 6,000 / 5,000 / 2,600	90	93	6.2	4.4 / 2	6.4 / 162	



PRODUCT#	DRIVE SIZE	BREAKAWAY Torque Ft. LBS. / NM	AIR Consumption CFM	AIR INLET NPT	IMPACTS PER Minute	DESIRED AIR Pressure PSI	FREE SPEED RPMS	MINIMUM HOSE Size ID	SOUND LEVEL DB(A)	VIBRATION LEVEL M/S2	WEIGHT LBS. / KG.
AWP075	3/4"	1,560 / 2,115	7.2	3/8"	950	90	5,500	1/2"	97.8	10.7	8.4 / 3.8

## POWER TOOLS AIR IMPACT WRENCHES

MPF970501

1/2" DRIVE ALUMINIUM

· Variable-speed trigger for speed control

torque to remove stubborn bolts

· Textured anti-slip comfort grip

· Three-position power regulator

**IMPACT WRENCH** 

reverse breakaway torque

1,490 NM. BREAKAWAY TORQUE



PRODUCT #	DRIVE SIZE	BREAKAWAY TORQUE Ft. LBS. / NM	AIR CONSUMPTION CFM	AIR INLET NPT	IMPACTS PER MINUTE	FREE SPEED RPMS	MINIMUM HOSE Size ID	SOUND LEVEL DB[A]	VIBRATION LEVEL M/S2	WEIGHT LBS. / KG.
MPF970501	1/2"	1,100 / 1,490	5.2	3/8"	1,030 / 1,120	6,260	3/8"	90	5.2	5.2 / 2.8



AWP599A 1" DRIVE ALUMINUM **IMPACT WRENCH** 

- · Twin-hammer mechanism
- · Aluminum two-piece construction
- · Multi-position power regulator
- Variable-speed throttle

PRODUCT#	DRIVE SIZE	BREAKAWAY TORQUE Ft. LBS. / NM	AIR CONSUMPTION CFM	AIR INLET NPT	IMPACTS PER Minute	FREE SPEED RPMS	MINIMUM HOSE Size ID	SOUND LEVEL DB[A]	VIBRATION LEVEL M/S2	WEIGHT LBS. / KG.			
AWD599A-6	1"	3,000 / 4,068	8.6	1/2"	720	5,700	3/4"	102	15.2	24.2 / 11.0			
AWP599A	1"	3,000 / 4,068	8.6	1/2"	720	4,400	3/4"	103.4	16.7	22.7 / 10.3			








# 5 POWER LIGHTWEIGHT 3,390 NM. OF BREAKAWAY TORQUE 368 MAL

#### 1" DRIVE AIR IMPACT FEATURES:

- Excellent power-to-weight ratio
- 3,390 Nm of Breakaway torque
- Easy access forward / reverse and regulator control
- Oversized D-handle allows use with gloves
- 2-Stage trigger for more control
- Comfort grip for low vibration

#### AWD099-6

1" DRIVE D-HANDLE IMPACT WRENCH 6" Extended anvil







AWP099
1" DRIVE IMPACT WRENCH





3,390 Nm for the most demanding applications



COMFORT GRIP

For low vibration Composite body for low weight



LIGHTWEIGHT RUBBER BUMPER

For durability



2-STAGE TRIGGER

For more control

PRODUCT#	DRIVE SIZE	BREAKAWAY Torque Ft. LBS. / NM	AIR CONSUMPTION CFM	AIR INLET NPT	IMPACTS PER Minute	DESIRED AIR Pressure PSI	FREE SPEED RPMS	MINIMUM Hose Size ID	SOUND Level DB[A]	VIBRATION Level M/S2	WEIGHT LBS. / KG.	LENGTH In. / MM
AWD099-6	1"	2,500 / 3,390	12	1/2"	1,000	90	5,000	3/4"	105	15.6	17.9 / 8.1	19.4 / 492.8
AWP099	1"	2,500 / 3,390	12	1/2"	900	90	5,000	3/4"	100.9	6.87	16 / 7.3	9.6 / 243.8

resulting in less fatigue

# POWER TOOLS AIR IMPACT WRENCHES

GET INTO THOSE
TOUGH-TO-REACH
PLACES
WITH THE

MIGHTY
MINI



#### MINI IMPACT WRENCHES


#### SUB-COMPACT SIZE, BIG POWER!

- Variable-speed trigger for maximum operator control
- One-hand power adjustment with three settings
- One-hand forward/reverse system
- Rubber grip that is resistant to automotive fluids
- Anti-marring rubber bumpers for protection
- Short 4.4" body to get in the tightest spots
- 861 Nm (AWP050M) of breakaway torque for most demanding applications





AWP050M 1/2" DRIVE MINI IMPACT





# POWER TOOLS AIR RATCHETS

#### MPF59025

#### 1/4" AND 3/8" DRIVE COMPACT AIR RATCHET

- Compact sealed-head design allows for use in tight and restricted spaces
- Dual-drive system enables easy changing between 1/4" and 3/8" drive providing added versatility over traditional fixed-anvil designs
- Forward / reverse lever positioned for ergonomic one-handed direction changes while in use



#### MPF59038

#### 3/8" AND 1/2" DRIVE HIGH-POWER AIR RATCHET

- Dual-drive system enables easy changing between 3/8" and 1/2" drive providing added versatility over traditional fixed-anvil designs
- Withstands up to 237.3 Nm (175 ft/lbs.) of manually applied torque
- Integrated clutch with two settings to enable control and reduce busted knuckles





#### ARP538

#### 3/8" DRIVE PALM **COMPOSITE AIR RATCHET**

- · Lightweight impact-resistant
- · Composite body
- · Cushion-grip to reduce vibration
- · Lever handle for throttle control
- Rotating air inlet
- · Triple planetary gear design





PRODUCT#	AIR Consumption CFM	AIR INLET NPT	IMPACTS PER MINUTE	BORE Diameter In. / MM	CHISEL SHANK Opening	STROKE LENGTH In. / MM	MINIMUM Hose Size ID	VIBRATION LEVEL M/S2	WEIGHT LBS. / KG.	LENGTH IN. / MM
MPH1911	2.6	1/4	2,400	.83 / 21	.401	3-3/4" / 95.25	3/8	10.4 in	5.4 / 2.45	9-1/2" / 241.3
MPH1931	3.2	1/4	3,100	.83 / 21	.401	2-1/3" / 50.8	3/8	7.4 in	4.6 / 2.09	7-5/16" / 177.8



AIR DIE GRINDERS AND SANDERS

## POWER TOOLS AIR DIE GRINDERS AND SANDERS





1/4" DRIVE COLLET 0.3HP MOTOR 90° DIE GRINDER



1/4" DRIVE COLLET 0.3HP MOTOR 120° DIE GRINDER

-											
ı	PRODUCT #	HORSE POWER Motor HP	COLLET	AIR Consumption CFM	AIR INLET NPT	FREE SPEED RPMS	MINIMUM HOSE Size ID	SOUND LEVEL DB[A]	VIBRATION LEVEL M/S2	WEIGHT LBS. / KG.	LENGTH In. / MM
	AG325AH90	0.3	1/4"	2.7	1/4"	23,000	3/8"	85.9	4.54	1.2 / 0.54	6.5" / 165.1
	AG325AH120	0.3	1/4"	2.7	1/4"	24,000	3/8"	84.8	5.22	1.2 / 0.54	7.5" / 190.5
	AG325S	0.3	1/4"	2.7	1/4"	30,000	3/8"	84.8	2.42	1 / .045	6.3" / 160
	AG325SE	0.3	1/4"	2.7	1/4"	28,000	3/8"	83.3	2.86	1.5 / 0.68	10.3" / 261.6





• 4" Extended straight head for tough to reach applications

## POWER TOOLS **BLOW GUNS**

#### BG1211

#### 11 PIECE PISTOL-GRIP **BLOW GUN KIT**

- · Durable cast aluminum body
- · High volume
- · Ergonomic comfort grip
- Large storage hook
- · Xtreme-Flo safety nozzle: Increase the velocity and volume of air exiting the nozzle while boosting the available thrust up to 250%
- · Quiet-Flo safety nozzle: Increases thrust while decreasing the amount of compressed air used. This nozzle reduces noise levels 6-20 dB less than conventional open air nozzles while providing a focused air stream
- Tri-Thrust safety nozzle: Provides a wider pattern ideal for cleaning a larger area of

- Needle tips (1"/2"/3"): Provide a precise, focused stream of air
- · Rubber tip: For use around delicate surfaces which can be easily scratched or marred

#### INCLUDES:

- 1 x Xtreme-Flo Safety Nozzle
- 1 x Rubber Tip • 3 x Needle Tips
- 2 x 12" Extensions
- 1 x Quiet-Flo Safety Nozzle
- 1 x Tri-Thrust Safety Nozzle
- 1 x Tip Adapter for ease of use
- Corrosion resistant metal tube



# POWER TOOLS **BLOW GUNS**

## POWER TOOLS **POWER TOOL ACCESSORIES**

# BG1201 **BLOW GUN WITH XTREME-FLO** SAFETY NOZZLE · Durable cast aluminum body · Variable-flow trigger Ergonomic grip • 1/4" NPT (female) inlet

#### **BG201D RUBBER-TIPPED BLOW GUN**

• 1/4" NPT inlet





#### BGB100

Variable control trigger

Large storage hook

thrust by up to 250%

 Xtreme-Flo safety nozzle increases the velocity and volume of air exiting the nozzle, while boosting the available

- · Durable, impact resistant materials designed for the shop
- · Unique rear facing hanging hook for ease of use
- Corrosion resistant metal tube



- Variable control trigger
- · Durable, impact resistant materials designed for the shop
- · Unique rear facing hanging hook for ease of use
- · Corrosion resistant metal tube
- · Adjustable flow knob for controlled, consistent air flow on every use

#### **BENT PIPE BLOWGUN** 300MM - RED

- Variable control trigger
- · Durable, impact resistant materials designed for the shop
- · Unique rear facing hanging hook for ease of use
- · Corrosion resistant metal tube



#### **PROTECTIVE BOOTS**

· Snug fit prevents slippage

· Colour helps identify your air tool

PRODUCT#	FOR USE WITH:	COLOUR	NOT SHOWN
PB760	AR760 Ratchet	Red	•
PB280Q	AW280Q / AW284Q Impact W.	Red	
PB3400R	AW3400Q Impact Wrench	Red	
PB4300	AW4300 Impact Wrench	Red	
PB850	AW850 Impact Wrench	Red	
PB038-050C-R	AWP038 / AWP050C Impact W.	Red	•
PB050-R	AWP050 Impact Wrench	Red	
PB075-R	AWP075 Impact Wrench	Red	
PB038M-050M-B	AWP038M / AWP050M Impact W.	Black	•
PB601G	12V Screwdriver	Green	
PB701G	12V Drill Driver	Green	
PB7010	12V Drill Driver	Orange	
PB801-901G	12V 1/4" Wrench / Driver	Green	•
PB801-9010	12V 1/4" Wrench / Driver	Orange	•
PB98-501G	MPF980 Impact Wrench	Green	•
PB98-5010	MPF980 Impact Wrench	Orange	
PB99-381G	MPF990381 / MPF990501C Impact W.	Green	•
PB99-3810	MPF990381 / MPF990501C Impact W.	Orange	•
PB99-501G	MPF990501-XJ Juggernaut	Green	
PB99-5010	MPF990501-XJ Juggernaut	Orange	
PBBWP038-B	BWP038 Impact Wrench	Black	•
PBBWP138-B	BWP138 / BWP150 Impact Wrench	Black	















PB050-R









PB99-5010

PB98-5010.

PBT70914

MASTER RATCHET PUMP KIT **DRILL ADAPTER** 





#### P032 1 QT. 4 OZ. PNEUMATIC AIR TOOL OIL · Long-life pneumatic oil for air tools

- · Metal adherence properties prevent lubrication loss from air pressure
- Protects neoprene O-rings and other plastic parts
- Available in 1 gt. (1.136 L) or 4 oz. (113.6 ml) sizes





- · Specially formulated for impact wrenches requiring grease
- Reduces noise levels greatly, inhibits rust, and protects against condensation





· Holds 3 oz. (85 ml) of light or heavy lubricant






\*Warning: Per OSHA standard 29 CFR 1910.242(b), blow guns should be regulated so as not to exceed 30 P.Sl.to avoid possible injury

## POWER TOOL ACCESSORIES

#### ADG31M

3/8" MANDREL -1/4" SHANK





#### ADG32M

1/4" AND 3/8" MANDREL -1/4" SHANK


· For use with air tools to adapt them to a 1/4" or 3/8" hole cut-off wheel



#### TD13MS

#### 13 PIECE TIP DRILL SET

- · Pin vise has magnetic cap with storage for bits
- Bits are extra long (1-7/8")
- Designed for drilling and cleaning fuel injectors, carburettor jets, water jets, welding and soldering tips, and electronics service/repairs
- Twelve high-speed steel twist drills (0.0225 to 0.063) and pin vise



#### VA502T **3 PIECE TITANIUM** STEP DRILL SET

- · Set drills twenty-eight holes from 1/8" to 3/4" diameter
- · Dual radial concave fluted, self-starting
- · Ideal for thin materials: sheet metal, plastic, and wood applications
- Includes three popular sizes in convenient storage pouch



	CONTRACTOR OF				
PRODUCT #	DESCRIPTION	DRILL SIZE	DRILLS	INCREMENTS	SET
VA502T	3 Piece Titanium Step Dril	l Set			
VA1T	Titanium Step Drill - 1	1/4"	(12) Holes: 1/8" - 1/2"	1/32"	•
VA2T	Titanium Step Drill - 2	1/4"	(6) Holes: 3/16" - 1/2"	1/16"	•
VAST	Titonium Ston Drill 2	2/0"	(0) Holoo 1//# 2//#	1/16"	

#### AH5512

.401 SHANK 1/2" DRIVE **AIR HAMMER SOCKET ADAPTER** 







#### AH2605

.401-SHANK QUICK-RELEASE AIR HAMMER BIT RETAINER

- · Precision ground hardened steel components
- · Can be used with .401 shank tools and standard air hammer bits

# POWER TOOLS

**POWER TOOL ACCESSORIES** 



PRODUCT#	DESCRIPTION	BLADE SIZE MM / IN.	LENGTH MM / IN.	USES	SET
AHBK5P	Air Hammer Bit Kit	,			
AH8MP	Guide Driver Bit	6.4 / 1/4"	152.4 / 6"	_	
AH902P	Tail Pipe Cutter Bit	25.4 / 1"	177.8 / 7"	For Cutting Tail Pipes with Curved Surfaces	•
AH907P	Claw Ripper Edging Tool Bit	19.1 / 3/4"	139.7 / 5-1/2"	For Cutting Body Panels	•
AH908P	Muffler Cutter Bit	12.7 / 1/2"	190.5 / 7-1/2"	Removes Clamp Type Mufflers	
AH909P	Panel Cutter Bit	19.1 / 3/4"	177.8 / 7"	-	٠
AH910NP	Flat Chisel with Narrow Blade Bit	12.7 / 1/2"	177.8 / 7"	-	
AH910P	Flat Chisel – Standard Bit	19.1 / 3/4"	177.8 / 7"	-	•
AH911P	Tapered Punch Bit	NA	177.8 / 7"	-	•
AH951P	Undercoat Scraper Bit	25.4 / 1"	171.5 / 6-3/4"	-	

#### .401 SHANK AIR HAMMER BITS

- · Fully hardened and tempered shock resistant tool steel
- · Black-oxide finish to prevent corrosion

PRODUCT#	DESCRIPTION
AH31960	.401 Shank Spot Weld Breaker Air Hammer Bit 6-1/4"
AH31962	.401 Shank Hammer Head Air Hammer Bit 1" x 8"
AH31964	.401 Shank Concave Hammer Air Hammer Bit 1" x 6"
AH31970	.401 Shank Scraping Air Hammer Bit 2" x 8-1/2"
AH31972	.401 Shank Cold Chisel Air Hammer Bit 5/8" x 6-1/4"
AH31975	.401 Shank Rivet / Bolt Cutting Air Hammer Bit 6-1/2"
AH31976	.401 Shank Scraper Air Hammer Bit 1-1/8" x 8"
AH31982	.401 Shank Hammer Head Air Hammer Bit 1" x 4-1/4"
AH31987	.401 Shank Hammer Air Hammer Bit 1" x 6"
AH32004	.401 Shank Ball Peen Hammer Air Hammer 1" x 6"
AH32008	.401 Shank U-Joint / Tie Rod Tool Air Hammer Bit 1" x 6"





#### **POWER TOOL ACCESSORIES**



#### AH32023

#### 5 PIECE .401 SHANK AIR HAMMER BIT SET

- Fully-hardened and tempered shock-resistant tool steel
- · Black-oxide finish to prevent corrosion



#### 4 PIECE .401 SHANK SPECIALTY HAMMER BIT SET

AH32024

- · Fully-hardened and tempered shock-resistant tool steel
- · Black-oxide finish to prevent corrosion



#### AH32025

#### 4 PIECE .401 SHANK HAMMER HEAD BIT SET

- Fully-hardened and tempered shock-resistant tool steel
- · Black-oxide finish to prevent corrosion

#### **5 PIECE STEPPED PICKLE FORK KIT**

- · Ideal kit for separating ball joints, steering dampeners, tie rods, Pitman arms, and other heavy-duty chassis and suspension applications
- Improved stepped fork design greatly reduce bounce back of the tool during heavy use
- · Complete set includes three stepped forks and two handles; one for hammering and one for use in an air hammer (.401" shank)
- Heavy-duty steel alloy forks withstand abuse and can be sharpened over the life of the tool

#### PFK41510

HANDLE FOR 5 PIECE STEPPED PICKLE FORK KIT

#### PFK41520

PNEUMATIC DRIVER FOR 5 PIECE STEPPED PICKLE FORK KIT



#### AH32028 5 PIECE .401 SHANK **EXHAUST AIR HAMMER BIT SET**

- · Fully-hardened and tempered shock-resistant tool steel
- Black-oxide finish to prevent corrosion



PFK41530 1 1/8" PICKLE FORK HEAD

PFK41540 15/16" PICKLE FORK HEAD

# POWER TOOLS

## **POWER TOOL ACCESSORIES**

#### **WIRE END BRUSHES**

- · Adhere to the highest standards and specifications in the industry
- Used for heavy-duty cleaning of large or small metal surfaces, they will attack weld scaling and corrosion, and are very effective for cleaning prior to welding, rust and paint removal, steel tank cleaning, and many other cleaning and rust removal applications

PRODUCT#	DIAMETER X LENGTH	RPM	STYLE
EB118X1KT	1-1/8" x 1"	20000	Knotted on 1/4" Shaft
EB12VT	1/2" x 1-1/8"	20000	Crimped on 1/4" Shaft
EB134X34TCS	1-3/4" x 3/4" Trim	4500	Crimped on 1/4" Shaft
EB1X118ST	1" x 1-1/8"	20000	Crimped on 1/4" Shaft
EB234X78CS	2-3/4" x 7/8" Trim	4500	Crimped on 1/4" Shaft
EB34X1ST	3/4" x 1"	20000	Crimped on 1/4" Shaft





#### 7 PIECE GRIND AND DEBURR STONE SET

- · Assortment of aluminium-oxide grinding points
- · Excellent for general grinding, polishing, and deburring
- 1-1/2" Long x 1/4" diameter shanks

INCLUDES	DIAMETER MM / IN.	THICKNESS MM / IN.	RPM
Porting Wheel	19.1 / 3/4"	63.5 / 2-1/2"	19800
Porting Wheel	19.1 / 3/4"	31.8 / 1-1/4"	48000
Mounted Point	9.5 / 3/8"	25.4 / 1"	55200
Mounted Point	12.7 / 1/2"	38.1 / 1-1/2"	30370
Mounted Point	17.46 / 11/16"	6.4 / 1/4"	48000
Mounted Point	25.4 / 1"	25.4 / 1"	34500
Mounted Point	31.8 / 1-1/4"	6.4 / 1/4"	30560



#### VRSAW9

#### 9 PIECE GENERAL PURPOSE **COARSE STONE SET**

- Assortment of coarse 24-grit abrasive, multi-purpose grinding wheels
- Fast stock removal; for mild steel and cast iron-high removal rate

THICKNESS MM / IN.  31.8 / 1-1/4"  31.8 / 1-1/4"  25.4 / 1"	48000 45750
31.8 / 1-1/4"	45750
25.4 / 1"	25250
	35250
25.4 / 1"	34500
28.6 / 1-1/8"	45000
9.5 / 3/8"	38200
15.9 / 5/8"	38200
25.4 / 1"	34500
25.4 / 1"	35620
	25.4 / 1" 28.6 / 1-1/8" 9.5 / 3/8" 15.9 / 5/8" 25.4 / 1"



## **POWER TOOL ACCESSORIES**



#### **CARBIDE BURRS**

- For use with 1/4" high-speed grinders
- · Removes burrs from sheet metal or cast iron
- · Cleans up welding areas
- Maximum RPM rating of 30,000

PRODUCT#	FLUTE MM / IN.	HEAD MM / In.	SHAPE		SET	
CB5S	5 Piece Miscellar	neous Carbide Burr	Set			
CB4S	4 Piece Miscellar	neous Carbide Burr	Set			
CB3NFS	3 Piece Non-Ferr	ous Carbide Burr S	et			
CBA1	19.1 / 3/4"	6.4 / 1/4"	Cylindrical		•	٠
CBA5	25.4 / 1"	12.7 / 1/2"	Cylindrical			
CBC3	19.1 / 3/4"	9.5 / 3/8"	Cylindrical / Radius End		٠	
CBC5CS	6.4 / 1/4"	12.7 / 1/2"	90° Cone			٠
CBC5NF	25.4 / 1"	12.7 / 1/2"	Cylindrical / Radius End	٠		
CBD5NF	11.1 / 7/16"	12.7 / 1/2"	Ball	•		
CBF3	19.1 / 3/4"	9.5 / 3/8"	Tree / Radius End			
CBF5	25.4 / 1"	12.7 / 1/2"	Tree / Radius End		٠	٠
CBL3	27 / 1-1/16"	9.5 / 3/8"	Taper (14° Angle)		•	
CBL3NF	27 / 1-1/16"	9.5 / 3/8"	14° Taper	•		
CBR3D	19.1 / 3/4"	6.4 / 1/4"	Diamond Cut Fibreglass Router			٠
CBR3FL	NA	6.4 / 1/4"	Carbide Router for Aluminium and Plexiglass			•

#### **3 PIECE LONG CARBIDE BURR SET**

- · Precision shanks are a full 6" long
- Heavy-duty burr heads
- Use with any of our 1/4" collet die grinders
- · Ideal for use in many aircraft applications
- · Removes burrs on most metals, cast iron, or welding areas

PRODUCT #	SHAPE	SIZE	SET
CB3L	3 Piece Long Carbide Burr Set		
CBC3L	Cylinder Radius End Burr	3/8"	•
CBE3L	Oval Carbide Burr	3/8"	•
CBF3L	Tree Radius Burr	3/8"	•





# POWER TOOLS

#### **POWER TOOL ACCESSORIES**



#### **ALUMINIUM OXIDE CUT-OFF WHEELS**

- · Double reinforced cut-off wheels provide long life
- · Designed to fit any air tool using a 2-7/8" - 3" wheel



#### TYPE 1 ALUMINIUM OXIDE **CUT-OFF WHEELS**

- · Double reinforced for durability
- · Available in various thicknesses and hole sizes, these wheels work on 4" cut-off tools

PRODUCT#	QUANTITY	GRIT	RPM	DIAMETER X THICKNESS X HOLE SIZE	TYPE
COW213238	10	60	25,000	2" x 1/32" x 3/8"	Aluminium Oxide
COWA3116ECON-50	50	54	25,000	3" x 1/16" x 3/8"	Aluminium Oxide
COW411638	10	46	21,000	4" x 1/16" x 3/8"	Type 1 Aluminium Oxide
COW413238	10	54	21,000	4" x 1/32" x 3/8"	Type 1 Aluminium Oxide

#### MSD6057 2" HOLDER PAD MSD6060 (NOT SHÓWN)

3" HOLDER PAD

- · Highest quality rubber holder pads with the standard 1/4" shank drive
- Roloc® style receiver for sanding and surface conditioning discs





#### MINI GRINDING DISC

- · Aluminium-oxide mini grinding discs are perfect for all your grinding needs where space is an issue
- Available in 2" or 3" with a 3M® compatible button, they are a heavy resin fibre material for extra strength and durability

PRODUCT#	DIAMETER X HOLE	GRIT	RPM
MGDA0280	2" x Twist to Lock Button	Aluminium Oxide 80	25,000
MGDA0350	3" x Twist to Lock Button	Aluminium Oxide 50	20,000



#### 2" MINI GRINDING DISCS

- · Reinforced for strong, durable long life usage
- · They can get into small corners where others can't

PRODUCT #	DIAMETER X THICKNESS X HOLE SIZE	GRIT	RPM
DCAGD218120	2" x 1/8" x 3/8"	Aluminium Oxide 120	20,000
DCAGD21860	2" x 1/8" x 3/8"	Aluminium Oxide 60	20,000
DCAGD21880	2" x 1/8" x 3/8"	Aluminium Oxide 80	20,000

#### DEPRESSED-CENTRE ALUMINIUM-OXIDE GRINDING WHEELS

- · For all your heavy-duty grinding needs
- · Made of reinforced aluminium oxide material

PRODUCT #	DIAMETER X THICKNESS X HOLE SIZE	GRIT	RPM
DCGD41458	4" x 1/4" x 5/8"	Aluminium Oxide 24	13,700
DCGD45145811NC	4-1/2" x 1/4" x 5/8"	Aluminium Oxide 24	11,900
DCGD451478	4-1/2" x 1/4" x 7/8"	Aluminium Oxide 24	11,900





## POWER TOOL ACCESSORIES

# POWER TOOLS AIR HOSES AND COUPLERS









MSD0485 3" MEDIUM

MSD0486 3" VERY FINE



3" COARSE







AS517-42

AS3MS-IH-PAD

#### **REPLACEMENT PADS**

PRODUCT #	PAD FACE	PAD SIZE	PAD TYPE	USE WITH TOOL:
AS6MS-JH-PAD	J-Hook	6"	Tapered Edge Non-Vac	AS6MS
AS6MS-JHV-PAD	J-Hook	6"	Tapered Edge Vacuum	AS6MS
AS3MS-JH-PAD	J-Hook	3"	Tapered Edge Non-Vac	AS3MS
AS517-42	N/A	3'	N/A	AS517



QUICK-CHANGE SURFACE CONDITIONING DISCS

• Designed to remove gaskets, sealants, and corrosion

quickly without loading the disc's cutting surface · Extremely durable and will fit all Roloc® style holder pads



32 TPI SUPER DUTY AIR SAW BLADE

# ASB984A (ORDER IN PACKS OF 10)



#### RP901375

#### **REUSABLE SPLICER** 3/8" FLEXZILLA® AIR HOSE

- · Reusable anodized aluminium hose splicer
- · Easily repair hose using two wrenches



#### RP900375

#### **REUSABLE END** 3/8" FLEXZILLA® AIR HOSE

- · Reusable NPT anodized aluminium fitting
- · Spiral bend restrictor increases hose flexibility
- · Easily repair hose using two wrenches



#### 3/8" FLEXZILLA® AIR HOSES

- · Made from engineered hybrid polymer to flex easily and will not kink in cold weather
- · Lightweight and easy to handle
- · Excellent abrasion resistance to reduce damage when dragged
- · Reinforced bend restrictor

PRODUCT#	DIAMETER In. / MM	LENGTH In. / MM
HFZ3825YW2	3/8" / 9.5	25' / 7.6
HFZ3850YW2	3/8" / 9.5	50' / 15.2



#### HFZ38250YW FLEXZILLA® BULK AIR HOSE

- · Extreme all-weather flexibility, even in sub-zero temperatures (-40 to 140° F)
- · Lays flat, no memory
- Superior bend radius
- · Kink-resistant under pressure
- · Maximum working pressure: 300 PSI
- · 3:1 Safety factor
- · Excellent abrasion-resistant outer cover
- Made from premium hybrid polymer

DIAMETER IN. / MM	LENGTH IN. / MM
2/0" / 0 5	2501 / 75 2



Made from engineered hybrid polymer so it's easy to flex and will not kink in cold weather

• Excellent abrasion resistance to reduce damage

· Lightweight and easy to handle

#### L8305FZ

HFZP3806YW2B 3/8" X 6' BALL SWIVEL WHIP HOSE

when dragged · Reinforced bend restrictor

#### 3/8" X 50' FLEXZILLA® **AIR HOSE REEL**

- Unique winding system automatically layers hose ensuring that the hose is coiled smoothly, easily, and every time
- · Adjustable hose stopper increase or decrease the length of the hose that remains when hose is fully retracted
- · 7-Position locking bracket can swivel freely on a mounting bracket up to 135°
- Latching mode switch latches hose every 3' or immediate automatic rewinding
- Extra large swivel a 3/4" swivel inlet reduces flow restrictions and allows for Maximum flow
- · Freestanding base allows reel to rest on ground
- Kink-resistant under pressure
- Extreme all-weather flexibility, even in sub-zero temperatures (-40 to 140° F)
- · Maximum working pressure: 300 PSI
- · 3:1 Safety factor
- · Excellent abrasion-resistant outer cover

DIAMETER IN. / MM	LENGTH IN. / MM
3/8" / 9.5	50' / 15.2







• 1/4" Male x 1/4" female NPT

Infinitely adjustable







NOTES	NOTES		
			/ /
			/
			7
			_44
;/		370 - V - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1	

