

AUTOMOTIVE SPECIALITY

CONTENTS:

| A/C LEAK DETECTION |
|----------------------------------|
| A/C SERVICE TOOLS |
| BATTERY & RADIATOR |
| ELECTRICAL SYSTEM TESTERS |
| BATTERY SERVICE |
| COOLING SYSTEM SERVICE |
| BRAKE & WHEEL |
| TYRE INFLATION |
| AXLE NUT SOCKETS |
| WHEEL NUT SOCKETS |
| BRAKE TOOL SETS |
| TUBING CUTTERS |
| FLARING TOOLS |
| BRAKE SPRING TOOLS |
| BRAKE PAD TOOLS |
| BRAKE BLEEDERS |
| DIAGNOSTICS |
| CIRCUIT AND FUSE TESTERS |
| TEST LEADS AND ACCESSORIES |
| SOLDERING TOOLS |
| RELAY SERVICE KITS |
| TRAILER CONNECTOR MAINTENANCE |
| TERMINAL REPAIR |
| LEAK EVAP DETECTORS |
| |

MACTOOLS.CO.UK 0114 291 7266

| | PAINT & BODY | |
|----|-----------------------|-----|
| 70 | TIN SNIPS | 305 |
| 71 | SPRAYING | 305 |
| | EQUIPMENT | 306 |
| 72 | HAND TOOLS | 307 |
| 73 | AIR HAMMER TOOLS | 314 |
| 74 | WELDING AND CUTTING | 314 |
| | SPECIALITY TOOLS | |
| 78 | DRIVE TRAIN | 315 |
| BO | IGNITION | 322 |
| 82 | FUEL | 324 |
| 84 | EMISSIONS | 326 |
| B4 | TESTING | 327 |
| 86 | PULLERS | 330 |
| 87 | EQUIPMENT | 333 |
| 87 | STEERING & SUSPENSION | |
| 89 | BALL JOINT TOOLS | 336 |
| | TIE ROD TOOLS | 337 |
| 90 | ALIGNMENT TOOLS | 338 |
| 94 | STEERING TOOLS | 339 |
| 98 | GREASE GUN TOOLS | 340 |
| | | |

301

299

302

304

11





Backlit display

| PRODUCT # | ACCURACY | BATTERY LIFE Approx. Hours | DISPLAY Illumination | EMISSIVITY | FIELD OF View Ratio | MODES | NON-CONTACT Temperature Range | POWER OFF | RESOLUTION | RESPONSE Time | TARGET Indicator |
|-----------|-------------------|-------------------------------|-------------------------|------------|------------------------|-------|-------------------------------------|--------------------------|-------------------|------------------|---------------------|
| AC52225C | ±2% of reading | 180 | Backlit Colour LCD | 0.95 | 12:1 | MAX | -76° to 1022°F (-60° to 550°C) | Auto after 15 seconds | 0.1° F/ 0.1° C | 1 Second | Dual Laser Spot |

AIR CONDITIONING A/C SERVICE TOOLS

AC72475 **UNIVERSAL HYDRAULIC FLARING TOOL KIT**

 Fabricates push-connect 1/4," 5/16," and 3/8"; for use with GM[®] fuel line flares, brake lines and transmission 5/16" and 3/8"; flare/double flare 3/16," 1/4," 5/16," 3/8," and 1/2"; metric bubble flare 4.75mm, 6mm, 8mm, and 10mm



AC70089A **2 PIECE TUBING CUTTER KIT**

INCLUDES:

• TCM130B Cutting Wheel Cuts hard or soft copper, aluminium, brass, thin wall steel, and stainless steel tubing.

Heavy-Duty mini cutter is designed for applications with limited working space TC126A Cutting Wheel

Cuts copper, aluminium, or thin wall steel tubing. Clean right angle cuts with no burs or chips

TCM130B

TUBING CUTTER 1/8" - 5/8"

- Heavy-duty mini cutter is designed for applications with limited working space
- Cuts copper, aluminium, brass, thin-wall steel, and stainless steel tubing 1/8" - 5/8"

| | PRODUCT # | DESCRIPTION |
|--|-----------|---|
| | AC70089A | 2 Piece Tubing Cutter Kit |
| | TC126A | Heavy-Duty Tube Cutter 1/ (3-28mm) O.D. Tubing (1/4" |
| | TCM130B | Mini Tube Cutter 1/8" (3-16mm) O.D. Tubing (1/8" |

TC126A TUBING CUTTER 1/8" - 1-1/8"

- Cuts copper, aluminium or thin-wall steel · Makes right angle cuts with no burrs or chips









TCM130B





MT3809A / MT3809A-OR / MT3809A-GR **40-1200 CCA ELECTRONIC BATTERY AND SYSTEM TESTER**

- · Features an operating range of 7-15V and the capacity to test batteries rated between 40-1200 CCA
- · It adds the convenience of starting and charging system testing and offers quick assessment, providing both a numerical result and a pass/fail result
- · Reverse polarity and over-voltage protection
- Small, portable, pocket-sized
- Tests multiple battery types
- Wide operating range

BT3180D **DIGITAL BATTERY LOAD TESTER /** CHARGING SYSTEM ANALYSER

- · Performs state of charge, battery load test,
- and starting system test
- Microprocessor controlled 12V Only
- 100-Amp Load test

B120BDM OBDII MEMORY SAVER

- Developed to protect the internal memory of the car when the battery is disconnected. (radio, diagnosis code ...)
- This unit is connected via the OBDII port of the car to the booster, which acts as an external battery
- For all 12 Volt vehicles
- 16 point OBD plug. OBDS / EODS

BATTERY SERVICE

L54150 **BATTERY TERMINAL /** WIPER ARM PULLER

- Removes battery terminals and bolted on wiper arms
- · Tighten knurled cone to force jaws under the cable clamp
- Turn centre screw to lift clamp off terminal Also removes bolted on windshield wiper arms
- that fit over a tapered spline • The puller screw pad is designed to fit the top of the spline post for easy pulling

BATTERY & RADIATOR

BPKIT2 **7 PIECE BATTERY TOOL KIT**

| PRODUCT # | DESCRIPTION |
|-----------|--------------------------------|
| BPKIT2 | 7 Piece Battery Tool Kit |
| BTB541 | 4-in-1 Terminal Cleaner |
| BCS720 | Battery Terminal Spreader/Clea |
| BP21K | Battery Terminal Lifter |
| BP23K | Battery Terminal |
| BP25K | Battery Pliers |
| BP26K | Battery Terminal Ratchet |
| BP27K | Battery Terminal Ratchet Exter |

BT3180D

15A SMART BATTERY CHARGER

- 100% Automatic
- · Charge all lead acid batteries: liquid, VLRA, AGM, gel
- · Start, Stop battery, and vehicles compatible
- 6-Language interface
- Polarity inverting protection
- Wrong voltage protection
- No Spark technology
- · 8-Step intelligent charging program · Battery maintainer mode
- Output voltage limited at 14.7V
- Advanced showroom mode












BT12 BATTERY HYDROMETER

- Small tip permits easy entry into small 12V batteries
- Temperature compensating
- Accurate to within .003 gravity points

BCC796 **BATTERY CABLE CUTTERS**

- Precision-ground blades cleanly cut without distorting soft copper cable
- 6" (152.4mm) handles for extra pressure
- Ground blade guide to minimize deflection
- Jam nut on joint to maintain even pressure on ground inside surface of blades
- Capacity: Up to and including 2/0 cable
- Overall length: 9" (228.6mm)





MTPROG **12V PRO BOOSTER PACK**

- Integrated battery charger within the booster
- · Power fuse for increased safety & protection against short circuit or overcharge
- · Updated heavy duty clamps
- High current capability for use on old / worn engines
- · Light, workshop fluid resistant casing with easy transport handle





BATTERY & RADIATOR **COOLING SYSTEM SERVICE**

BR6 **BATTERY TERMINAL RESHAPER**

• Reshapes negative and positive posts while improving electrical connections One tool provides a perfect match for posts and terminal clamps



BTB1A **BATTERY POST** AND CABLE CLEANER

- · Protective cover fits both ends · Clean top terminals and top posts
- Ensures a great connection between battery cable and battery

107A **PROPYLENE GLYCOL ANTIFREEZE TESTER**



- · Tests all propylene glycol based antifreeze including Sierra®
- The number of floating discs indicates the degree of coolant protection
- · Temperature compensating with
- both Fahrenheit and centigrade scales
- · Durable break-resistant plastic housing

BATTERY & RADIATOR **COOLING SYSTEM SERVICE**

UCT750C **UNIVERSAL COOLING SYSTEM PRESSURE TESTER**

- · Universal radiator adapter that fits every vehicle, eliminating the need for multiple adapters forever
- · Elastomeric adapters are engineered with varying durometer ratings, ensuring maximum versatility and performance
- · Expands to fit every vehicle and works with any pressure pump



PT730MB **COOLING SYSTEM** PRESSURE TESTER

- Test all systems from 4 PSI to 30 PSI caps and 1.36kg to 13.6kg (3 lb. to 30 lb.)
- · Large special coated barrel quick pump
- Easy-to-read professional 2-1/2" gauge
- Compatible with all testing adapters offered by Mac Tools®

TP727B REFRACTOMETER WITH AUTOTEMP

- Test propylene glycol including Sierra®
- Test ethylene glycol including Dexcool[®]
- · Calibration adjustment screw
- · Auto-temperature adjustment
- Adjustable lens focus

SCALE RANGE:

- E: -64° to 0° C
- P: -51° to 0° C
- B: 1.100 to 1.400sg









106A **ETHYLENE GLYCOL** ANTIFREEZE TESTER

- Tests all ethylene glycol based antifreeze including Dexcool®
- · Temperature compensating with both Fahrenheit and centigrade scales
- · Durable break-resistant plastic housing

17972 4.5 GALLON **OVAL DRAIN PAN, BLACK**

- For easy transfer of liquids
- 6.25" pan height to fit tight spaces
- High-density polyethylene material
- is resistant to chemicals and solvents
- · Easy-to-clean



FEATURES

- High carbon, heat-treated steel construction
- Positive clamping without springs or adjustments
- For pinching off flexible fuel, brake, and vacuum hoses
- Black-oxide finish

HCP554 **MINI HOSE PINCH-OFF PLIERS**

HCP555 AUTOMATIC **PINCH-OFF PLIERS**

HCP556 **HEAVY-DUTY LARGE AUTO PINCH-OFF PLIERS**


| PRODUCT # | O.D. CAPACITY | OVERALL LENGTH | WEIGHT [OZ.] |
|-----------|---------------|----------------|--------------|
| HCP554 | 3/4" | 5-1/2" | 4 |
| HCP555 | 1-3/4" | 9-1/4" | 12.5 |
| HCP556 | 2-1/2" | 13-3/4" | 19 |

COOLING SYSTEM SERVICE

HCP733A **STANDARD STRAIGHT HOSE CLAMP PLIERS**

• Standard straight hose clamp pliers for removal of metal or plastic self-tightening hose clamps 11/16" - 2-1/2"





HC HC HCF

> HP HP

PISTOL-GRIP PINCH OFF PLIERS

- Angled design allows for access to areas some straight pliers cannot reach
- Self-locking mechanism holds pliers to hose with a simple squeeze



REMOVAL PLIERS

• Used to remove 3/16" to 1/2" vacuum and fuel hoses

P0P11 SMALL PISTOL-GRIP **PINCH-OFF PLIERS**



P0P13 LARGE PISTOL-GRIP **PINCH-OFF PLIERS**

276







HCP734A FLAT BAND HOSE **CLAMP PLIERS**

• Use to install and remove flat type hose clamps • Pliers latch in position to hold clamp • Swivel jaws grip at any angle

HC4SET 4 PIECE HOSE CLAMP PLIERS SET

• One-hand locking style

- Access open hard-to-reach flat band hose clamps
- Pinch and lock closed vent, radiator, vacuum, and fuel hoses/lines
- · Pinches off and locks rubber tubing or lines
- · The round nose profile prevents damage of hoses

| RODUCT # | DESCRIPTION | SIZE | JAW THICKNESS | THROAT Depth | SET |
|----------|------------------------------|------|---------------|-----------------|-----|
| 4SET | 4 Piece Hose Clamp Pliers Se | t | | | |
| P900 | Locking Hose Clamp Pliers | 7" | - | - | • |
| P901 | Locking Hose Clamp Pliers | 9" | - | - | • |
| P900 | Pinch-Off Pliers | 7" | 1/4" | 1" | • |
| P901 | Pinch-Off Pliers | 9" | 1/4" | 4" | • |



MC4200 **MULTI-CUTTER WITH REVERSIBLE BLADE**

• Cuts flexible hose up to 1-1/4" · Comes with loop for safe storage • Double-sided long-lasting blade





MAC VI



PSR7DR

7 PIECE MAC-GRIP[™] RADIATOR PICK SET

 Specifically-designed for ease of access into tight or unique spaces, providing leverage in close quarters, positioning or retrieval of parts and easily manoeuvre around obstacles that otherwise would be troublesome

| PRODUCT # | DESCRIPTION | BAR LENGTH In. / Mm | OVERALL LENGTH In. / Mm | SET |
|-----------|--|------------------------|----------------------------|-----|
| PSR7DR | 7 Piece Mac-Grip [™] Radiator Pick Set - Red | | | |
| RADP1DR | Mac-Grip [™] Hose And Clamp Pick - Hi-Vis | 6" / 152 | 10-3/4" / 273 | • |
| RADP2DR | Mac-Grip™ Hose Puller - Hi-Vis | 6" / 152 | 10-3/4" / 273 | • |
| RADP3DR | Mac-Grip™ Offset Hose Pick - Hi-Vis | 6" / 152 | 10-3/4" / 273 | • |
| RADP4DR | Mac-Grip [™] Long Reverse Offset Hose Pick - Hi-Vis | 10" / 254 | 14-3/4" / 375 | • |
| RADP5DR | Mac-Grip [™] Long Bent Offset Hose Pick - Hi-Vis | 10" / 254 | 14-3/4" / 375 | • |
| RADP6DR | Mac-Grip [™] Long Offset Hose Pick - Hi-Vis | 10" / 254 | 14-3/4" / 375 | • |
| SWL70DR | Mac-Grip [™] 90° Hook And Pick - Hi-Vis | 5" / 127 | 9-3/4" / 248 | • |



QLC90 TYRE CHUCK QUICK-LOCK

- 90° Lock-on chuck
- Quick-release knob
- Closed end valve style for air supply directly from air line
- 1/4"-18 FNPT with 5/8" hex nut
- Overall length: 5-9/16"

<mark>tg400</mark> Locking Straight-on Chuck

- Dual foot 1/4" Female NPT
- Dual lock
 Deep well lock
- Locks on valve when tilted
- For hard-to-reach valves

replaces valve cores • Operates like a screwdriver • Comfort-Grip™ handle

2-IN-1 COMBINATION VALVE CORE TOOL

TG570

VT43P

DUAL END

TYRE GAUGE - 12"

30° Reverse chuck

• Range: 10 - 150 PSI

VALVE CORE TOOL

Slotted end removes and

• Use on Budd style tyre valves

One end for large bore, one end for standard sizes
Heavy-duty firm grip



DT150-38CV Digital tyre gauge With straight chuck

- Range: 0 160 PSI
- 2" Dial with 17-1/2" hose
- Temperature and pressure compensation
- Bleed feature
- Increments of 1.0 PSI

278





14100470 Tyre valve installer

- Swivel head screws onto cap thread of tyre valve
- Handle is used as a lever to pull tyre valve into rim hole
- Overall length: 11-3/4"

<mark>S445</mark> Valve Repair Tool

- Re-threads inside and outside of valve stem
- Inserts or removes cores
- Provides quick, easy removal of broken cores

TDG120 DIAL TYRE 2-IN-1 GAUGE

- Fully-geared 1/32"(1mm) increment precision brass movement
- Shock-absorbing protective cover
- Pressure Range: 8-120 PSI
- 2 PSI (20 kPa) Increments
- Tread Depth Range: 0-15/32" (0-12mm)
- Dial: 2" (50.8mm)



TGD100AA DIAL TYRE PRESSURE GAUGE

- Large 2" (50.8 mm) dial
- 14" (355.6 mm) hose
- Reads in pounds per square inch (PSI) and kilopascal (kPa)
- Bleeder valve

BRAKE & WHEEL AXLE NUT SOCKETS

AS4549B

3 PIECE 1/2" DRIVE AXLE NUT SOCKET SET - 12-PT.

- Featuring 39mm socket applications: 2008 - '10 Toyota® Land Cruiser; 2008 - '10 Toyota® Sequoia; 2007 - '10 Toyota® Tundra; 2008 Lexus® LX 570
- · Most popular axle nut sockets for larger automobiles and SUVs
- Blow-moulded case

| PRODUCT # | DESCRIPTION | SIZE [MM] |
|-----------|---|--------------|
| AS4549B | 3 Piece 1/2" Drive Axle Nut Socket Set - 12-I | PT. |
| 454930 | Axle Socket - 12-PT. | 30 |
| 454936 | Axle Socket - 12-PT. | 36 |
| 454939 | Axle Socket - 12-PT. | 39 |

TFL3-SET

3 PIECE 1/2" DRIVE THIN-WALL IMPACT SOCKET SET - 6-PT.

· Covers three of the most common wheel lug sizes on the market today · Thin-wall design allows access to wheel lugs where standard sockets will not fit

EXT3 (NOT SHOWN) **3" IMPACT EXTENSION**

| PRODUCT # | DESCRIPTION | DRIVE Size | SIZE |
|-----------|----------------------------|---------------|------------------|
| TFL3-SET | 3 Piece 1/2" Drive Thin-Wa | II Impact So | cket Set - 6-PT. |
| TFL-1921 | Thin Wall Impact Socket | 1/2" | 19-21mm |
| TFL-3413 | Thin Wall Impact Socket | 1/2" | 3/4"-13/16" |
| TFL-7815 | Thin Wall Impact Socket | 1/2" | 7/8"-15/16" |

TTWP

TRUCK AND TRAILER WHEEL PAN

- Fits tyre rims with 13-3/4" I.D. and larger · Handle compartments hold
- hub nuts out of the oil
- · Made of polypropylene for durability
- · Capacity: 88 oz.



WHEEL STUD CLEANING KIT

- · Allows for quick and easy stud cleaning
- Designed to be used with a cordless drill • Contains 1/2" drive hex bit, 1/2" drive quick
- change adapter, and six brush heads Includes brush/stud sizes: 12mm (7/16"),
- and 28mm (1-1/8")



- Extra deep to fit over various axle lengths
- · Works where standard sockets won't

| PRODUCT # | DESCRIPTION | SIZE MM |
|-----------|--|------------|
| AS4548B | 8 Piece 1/2" Drive Axel Nut Socke Set - 6-PT. | t |
| 454829 | Axle Nut Socket - 6-PT. | 29 |
| 454830 | Axle Nut Socket - 6-PT. | 30 |
| 454832 | Axle Nut Socket - 6-PT. | 32 |
| 454834 | Axle Nut Socket - 6-PT. | 34 |
| 454835 | Axle Nut Socket - 6-PT. | 35 |
| 454836 | Axle Nut Socket - 6-PT. | 36 |
| 454838 | Axle Nut Socket - 6-PT. | 38 |
| 454839 | Axle Nut Socket - 6-PT. | 39 |







SOCKET SET - 12-PT.

- Fits axle nuts and automatic transmission tail output shafts on Toyota[®], Lexus[®], Chrysler[®], Dodge[®], Jeep[®], Audi[®], VW[®], and BMW[®], as well as many other makes Blow-moulded case
- 7 PIECE 1/2" DRIVE AXLE NUT SOCKET SET - 6-PT.
- 1/2" drive chrome-molybdenum sockets for heavy-duty use Blow-moulded case

STLWH2 **TRUCK WHEEL HUB CLEANING TOOL**

 Impact rated • Removes rust, corrosion and other build-up from wheel stud, drums and tyre rim. · Replacement cleaning discs available

STLWH2PD

6 PACK TRUCK WHEEL HUB CLEANING TOOL **REPLACEMENT PADS**

280



STLSC-SET

- 14mm (9/16"), 16mm (5/8"), 22mm (7/8"),

| PRODUCT # | DESCRIPTION | SIZE [MM] |
|-----------|---|--------------|
| HT976B | 8 Piece 1/2" Drive Axle Nut Socke Set - 12-PT. | t |
| 97629 | Axle Nut Socket - 12-PT. | 29 |
| 97630 | Axle Nut Socket - 12-PT. | 30 |
| 97632 | Axle Nut Socket - 12-PT. | 32 |
| 97634 | Axle Nut Socket - 12-PT. | 34 |
| 97635 | Axle Nut Socket - 12-PT. | 35 |
| 97636 | Axle Nut Socket - 12-PT. | 36 |
| 97638 | Axle Nut Socket - 12-PT. | 38 |
| 97639 | Axle Nut Socket - 12-PT. | 39 |

| PRODUCT # | DESCRIPTION | SIZE MM | | |
|-----------|---|------------|--|--|
| AS4547C | 7 Piece 1/2" Drive Axle Nut Socket Set - 6-PT. | | | |
| 454729 | GM®, Ford®, Asian | 29 | | |
| 454730 | GM®, Asian | 30 | | |
| 454732 | Honda®, Chrysler® | 32 | | |
| 454734 | GM® | 34 | | |
| 454735 | GM® | 35 | | |
| 454736 | GM®, Ford®, Chrysler® | 36 | | |
| 454738 | Full-Size and SUVs | 38 | | |



STLWH1 WHEEL HUB CLEANING TOOL

• Attaches to 1/2" drive impact wrench · Resurfaces brake rotor hub section for

a cleaner mating surface with the wheel

STLWH1PD

6 PACK WHEEL HUB CLEANING TOOL REPLACEMENT PADS





3TWSS 3 PIECE WHEEL PROTECTIVE SOCKET SET

- · Thin wall design for tight access wheel lug openings
- · Polypropylene sleeve protects high end alloy wheels
- · Polypropylene insert protects lug nuts from damage Colour coded sleeves for easy identification
- Includes: 17, 19 & 21mm

WBR1904 **22 PIECE WHEEL BEARING REPLACEMENT KIT**

- For use on front wheel drive cars and light trucks
- · The wheel bearing adapters allow the user to replace the wheel bearings with the steering knuckle and strut assembly intact on the vehicle
- Eliminates the need for a front end alignment once completed

INCLUDES:

- 13 x Bushings
- 4 x Sleeves
- 2 x Sleeve Plates • 1 x Sliding Screw
- 1 x Nut
- Washers



DBL6-SETA 6 PIECE DOUBLE-DUTY FLIP SOCKET SET

• One end is a standard 6-PT. socket

• Other end is a twist socket, damaged wheel lug remover

| PRODUCT # | DESCRIPTION | NOMINAL Size in. | NOMINAL Size MM. |
|-----------|-----------------------------------|---------------------|---------------------|
| DBL6-SETA | 6 Piece Double-Duty Flip Socket S | et | |
| DBL-13A | Double-Duty Flip Socket | 13/16" | - |
| DBL-17MA | Double-Duty Flip Socket | - | 17 |
| DBL-19MA | Double-Duty Flip Socket | - | 19 |
| DBL-21MA | Double-Duty Flip Socket | - | 21 |
| DBL-78A | Double-Duty Flip Socket | 7/8" | _ |
| EXT3 | 3" Impact Extension | - | - |



STFL3SET **3 PIECE THIN WALL FLIP SOCKET SET**

- Dual-sided flip sockets cover the four most common metric lug nut sizes
- Plastic sleeves to protect wheels
- Thin wall design provides greater access than standard wheel lug sockets
- · Set includes 3" impact extension

INCLUDES: • 2 x Sockets

• 1 x 3" Impact extension



TFL6-SET **6 PIECE THICK AND THIN** FLIP SOCKET SET



• One end is a standard wall 6-PT., the other is a thin wall 6-PT. socket of the same size

WHEEL NUT SOCKETS



WTE1470 / WTE1463 WHEEL TORQUE EXTENSION SETS

| PRODUCT # | COLOUR | RATING FT-LBS. | SIZE | SE | T |
|------------|--------------|-------------------|----------|----|---|
| WTE1470 | 7 Piece Whee | el Torque Extens | sion Set | | |
| WTE1463 | 5 Piece Whee | el Torque Extens | ion Set | | |
| WTE1463-C | Gray | 100 | 1/2" | • | • |
| WTE1463-E | Blue | 80 | 1/2" | • | • |
| WTE1463-F | Yellow | 65 | 1/2" | • | • |
| WTE1463-I | White | 120 | 1/2" | • | • |
| WTE1463-K | Purple | 110 | 1/2" | | • |
| WTE1463-Q | Aqua | 140 | 1/2" | • | • |
| WTE1463-BB | Orange | 160 | 1/2" | | • |

TOOLS

282



| BRA | KE S | N/H | <i><i>Ξ<i>Ξ</i><i></i></i></i> |
|--|---|-----|--|
| A CONTRACTOR OF THE PARTY OF TH | A TO REAL PROPERTY AND A DESCRIPTION OF A D | | |

| PRODUCT # | DESCRIPTION | NOMINAL Size in. | NOMINAL Size Mm. | SET |
|-----------|------------------------------------|---------------------|---------------------|-----|
| TFL6-SET | 6 Piece Thick and Thin Flip Socket | t Set | | |
| TFL-13 | Flip Socket | 13/16" | _ | • |
| TFL-17M | Flip Socket | - | 17 | ٠ |
| TFL-19M | Flip Socket | - | 19 | • |
| TFL-21M | Flip Socket | - | 21 | ٠ |
| TFL-78 | Flip Socket | 7/8" | _ | • |
| EXT3 | 3" Impact Extension | - | - | • |



WTK1503 9 PIECE 1/2" DRIVE WHEEL TORQUE SET

| PRODUCT # | COLOUR | RATING FT-LBS. | SIZE IN. | SIZE MM | | |
|------------|--------------|---------------------------------|-------------|------------|--|--|
| WTK1503 | 9 Piece Whee | 9 Piece Wheel Torque Master Set | | | | |
| WTK1503-A | Brown | 100 | 13/16" | - | | |
| WTK1503-B | Orange | 80 | - | 21 | | |
| WTK1503-C | Gray | 100 | 3/4" | 19 | | |
| WTK1503-E | Blue | 80 | 3/4" | 19 | | |
| WTK1503-F | Yellow | 65 | 3/4" | 19 | | |
| WTK1503-G | Red | 80 | - | 17 | | |
| WTK1503-I | White | 120 | 7/8" | - | | |
| LOC1500Q* | Aqua | 140 | 7/8" | - | | |
| LOC1500BB* | Turquoise | 150 | - | 21 | | |

*Not available as an individual SKU

BRAKE & WHEEL BRAKE TOOL SETS

L44800 **HEAVY-DUTY BRAKE SPRING TOOL**

· Removes and installs larger springs that don't use an anchor pin

· Also works on springs with an anchor pin





BT97841A **COLOUR-CODED DISC BRAKE** LINING GAUGE

- · Easily identifies if pads are still good (green),
- should be watched (yellow), or need replacement (red) Excellent for your customer to understand why a brake iob is necessary

L48400 **BRAKE CLIP TOOL**

· For import cars with brake shoe hold-down clips

CF330 4-IN-1 HONE KIT

INCLUDES:

- Adjustable Foreign Car Brake Hone, 1/2" - 2-1/4" (12.7mm - 57.2mm)
- Adjustable Disc Brake Cylinder Hone,
- 1-1/4" 3-1/2" (31.8mm 88.9mm)
- Adjustable Brake Cylinder Hone, 3/4" - 2-1/2" (19.1mm - 63.5mm)

BP6596

DISC PAD MEASURING TOOL

Convenient Storage Box

• Adjustable Small Engine Cylinder Hone, 1-1/4" - 3-1/2" (31.8mm - 88.9mm)

- Colour-coded brake pad gauge allows for a definitive measurement of brake pads to determine remaining life Unique design allows for measurement on the vehicle
- without the removal of any components





TB410 TUBING BENDER PLIERS

• Bends 3/16", 1/4", 5/16", and 3/8" copper and steel tubing without kinking or collapsing

INCLUDES: • 2 x Investment Cast Adapters

TB441 3/16" TUBING BENDER PLIERS

· Head design bends tubing without collapsing the tube or marking the tube surface Handles are more than 3-1/4 apart for proper leverage, even when handling steel tubing

• Bends 3/16" brake lines in tight spots without kinking or flattening • Bends all types of 3/16" O.D. tubing



TUBING CUTTERS

TC030 TUBE CUTTER 3/8" - 1-1/8"

- · Heavy-duty mini cutter designed for
- applications with limited work space
- Cuts copper, aluminium, brass, thin wall steel, and stainless steel tubing
- · Cuts tubing 3/8" to 1-1/8" in diameter

70034-1 (NOT SHOWN)

REPLACEMENT CUTTING WHEEL FITS TC030



TTC157 TENSION TUBE CUTTER 3/16" - 7/8" (5MM - 22MM)

- · The constant pressure tube cutter utilizes a spring to keep consistent compression on the cutting blade to the tube
- · Allows the user to cut through thin walled steel tubing without having to continually
- tighten or readjust the cutter
- Accepts a tubing range of 3/16" 7/8" (5mm - 22mm)


TTC158


TENSION TUBE CUTTER 1/8" - 1-1/8" (3MM - 30MM)

- · The constant pressure tube cutter utilizes a spring to keep consistent compression on the cutting blade to the tube
- · Allows the user to cut through thin walled steel tubing without having to continually
- · tighten or readjust the cutter • Accepts a tubing range of 1/8" - 1-1/8" (3mm - 30mm)

284











AC70089A **2 PIECE TUBING CUTTER KIT**

| PRODUCT # | DESCRIPTION | |
|-----------|---|---|
| AC70089A | 2 Piece Tubing Cutter Kit | |
| TC126A | Heavy-Duty Tube Cutter 1/8" To 1-1/8" (3-28mm) O.D. Tubing (1/4" - 1" Nominal) | • |
| TCM130B | Mini Tube Cutter 1/8" To 5/8" (3-16mm) O.D. Tubing (1/8" - 1/2" Nominal) | • |



TCM130B

TC126A TUBING CUTTER 1/8" - 1-1/8"

- Cuts copper, aluminium or thin-wall steel
- Makes right angle cuts with no burrs or chips

TCW062 (NOT SHOWN) **REPLACEMENT CUTTING WHEEL** FITS TC126A

TCM130B TUBING CUTTER 1/8" - 5/8"

- Heavy-duty mini cutter is designed for applications with limited working space
- · Cuts copper, aluminium, brass, thin-wall steel, and stainless steel tubing 1/8" - 5/8"

TCW030 (NOT SHOWN) **REPLACEMENT CUTTING WHEEL** FITS TCM130B

BRAKE & WHEEL FLARING TOOLS



FT158A-3 (NOT SHOWN)

ADAPTER

TOOLS

5/16" DOUBLE FLARING

AC72475

UNIVERSAL HYDRAULIC

and 3/8"; GM® fuel line flares, brake lines and transmission 5/16"

and 3/8": flare / double flare 3/16," 1/4," 5/16," 3/8," and 1/2"; metric bubble flare 4.75mm, 6mm,

• GM[®] fuel line flare and brake lines

FLARING TOOL KIT

8mm, and 10mm

FT158B **DOUBLE FLARING TOOL**

- · Flares soft steel and copper tube
- · Includes five adapters: 3/16", 1/4", 5/16", 3/8", and 1/2"
- Reamer to remove burrs
- Forged wing nuts for strength





FS242 COMBO FLARING TOOL KIT

· Works on aluminium, copper, and soft steel tubing

INCLUDES:

286

- All Adapters and Tools Necessary for Single and Double Flaring (Standard and Metric) • 1 x ISO Bubble Flare

METRIC DOUBLE FLARE TOOL

FT159B

- Will flare soft steel and copper tube
- · Features forged wing nuts for strength
- INCLUDES:
- 1 x Reamer to Remove Burrs from Cut Tubing
- 5 x Adapters 4.75, 5, 6, 8, and 10mm



TOOL 3/16" X 4.75MM

- Flares 3/16" and 4.75mm tubing for Bubble or double flares • Easy grip handle makes
- flares on the vehicle easy · Easy line up hole for the tubing

HTBFT **BRAKE LINE FLARING**



CVB3080 **CV BOOT CLAMP** PLIERS EAR-TYPE

BSP592

S14AP

TRUCK BRAKE SPRING PLIERS

15/16" BRAKE SHOE RETAINING

BRAKE PAD TOOLS

SPRING COMPRESSOR

For Bendix[®] brakes

Larger Bendix[®] springs

· Designed to remove and install the brake shoe return springs on medium-duty and heavy-duty drum brakes

- · For all ear-type clamps, including late model GM[®] front wheel outboard CV joints
- · May be used with 1/2" torque wrench and breaker bar to crimp late model GM[®] outboard CV boot clamps to specification






S8AP

\$75F





BRAKE SPRING TOOLS















BST4510 BRAKE SPRING TOOL

• Designed for import car brake return springs • Removes and installs import and domestic brake springs that don't use an anchor pin



| PRODUCT # | BLADE WIDTH In. / Mm | MAKE | OVERALL LENGTH In. / MM |
|-----------|-----------------------------|-------------|----------------------------|
| S7AP | 1/2" / 12.7 | Chevrolet® | 6" / 152.4 |
| S8AP | 17/32" / 13.5 3/8" / 9.5 | _ | 7" / 177.8 |
| S75P | 17/32" / 13.5 | Oldsmobile® | 9" / 228.6 |
| S181P | 1/2" / 12.7 | Trucks | 16-3/4" / 425.5 |

\$75F

S181



CVB3050 **CV BOOT CLAMP** PLIERS EARLESS-TYPE

0000 · Designed for use on earless-type clamps, including those found on late model GM® inboard CV joints

287

BRAKE & WHEEL BRAKE PAD TOOLS

DBPS257 DUAL PISTON BRAKE PAD SPREADER

- · Compresses dual brake pistons simultaneously
- · Makes dual piston pad replacement a simple job



- Fast acting plunger compresses disc brake pistons in seconds · Makes brake pad replacement
- an easy job



4-IN-1 BRAKE PAD SPREADER

- · For both fixed and floating calipers
- · Fixed calipers: Twin and quad piston
- Floating calipers: Single and twin piston
- · Ensures parallel piston retraction on dual and quad piston calipers
- · Single lever mechanism used to apply and release force for ease of operation and faster service.

DBC5000 UNIVERSAL CALIPER TURN

AND PUSH-BACK TOOL

· Compresses any size brake caliper, from motorcycles, standard size cars. trucks and SUVs, and even 18 wheelers • A 3/8 ratchet can be inserted on the

BRAKE PAD TOOLS

- end of the tool for much easier use · Can also perform front brake jobs
- by flipping the head around
- · Eliminates need for sets with high piece counts



BHS2 **2 PIECE ORANGE CALIPER**

- · Holds brake calipers out of your way during brake, bearing, suspension, or axle work
- · Reduces possible brake hose damage

HANGER SET

7PBWS 7-PC. BRAKE WRENCH SET

- systems without removing the wheels
- For universal bleeder nipples
- 3' silicon hose with check valve for
- one-person brake bleeding

INCLUDES:

• 7, 8, 9, 10, 11, 12mm, and 3/8"

BCS700 7 PIECE DISC BRAKE CALIPER SET

- · Ideal for most brake applications
- S2 Industrial Strength Bits

INCLUDES:

- Hex Sizes 1/4", 5/16", 3/8", 8mm Plus T40, T45, and T50
- Blow-moulded case

BCTBT **BRAKE CALIPER**

- **TURN-IN TOOL** • Designed to rotate brake pistons back into the caliper on vehicles with self-adjusting parking brakes
- Replaces kits that contain up to 20 parts by having universally adjustable 2- and 3-pin configuration
- Fits on a standard 1/4" ratchet or breaker bar and works on both right- and left-hand pistons
- Works on most domestic and import vehicles that have self-adjusting parking brakes

2790470

4-IN-1 BRAKE CALIPER PRESS

- · Works on single, dual and quad calipers · Centrally distributes force to
- prevent misalignment of pistons
- 360° Ratchet swing allows
- access at any angle
- · Extended reversing lever allows for easy change from spreading to retracting



PB10500 PARKING BRAKE CABLE **COUPLER PLIERS**

- · Used on light/medium-duty trucks, SUV's & vans with drum or disc brakes, usually rear wheel drive
- · This set of angled pliers is heat treated and 14" length to safely separate the mid-cable coupler from the cable end

BRAKE & WHEEL BRAKE BLEEDERS





BB2000 BRAKE BLEEDER / EVAC

- · Variable thumb throttle holds desired flow rate
- · Swivel air inlet for flexibility of movement
- · Auto shutoff valve prevents overfilling
- Bleeds up to two quarts per minute

INCLUDES

- Fluid Evacuation Wand for Draining Fluid Reservoirs, Adapters
- Brake Fluid Refill Kit
- · Hook for Hanging Bleeder

PBT70852 800ML VACUUM BRAKE BLEEDER KIT

· Uses compressed air to generate deep vacuum

- and spillage
- · Internal shut off valve closes when not in use to prevent fluid spills when stored
- · Clear drain hose provides visible inspection
- of old fluid during bleeding
- Vacuum: 23 InHg at 100 psi
- Fitting: 1/4 BSP (not included)

288













· Ideal for bleeding brake and hydraulic clutch

to bleed old fluid and air from hydraulic brake systems · Reduces repair times increasing productivity and profit · Built-in safety valves to prevent accidental fluid spray



BRAKE & WHEEL **BRAKE BLEEDERS**

BHC96420

BRAKE HOSE CLAMP

· Chrome-plated steel construction

· Clamps off hoses without damage

2 PACK



BB2010RK **CLAMP-ON AUTO REFILL KIT**

- · Large 40 oz. (1.2L) capacity reservoir holds enough fluid for multiple brake jobs
- Adapters for standard 12 oz. (355 ml) and 32 oz. (946 ml) brake fluid bottles
- · Large stable base clamps securely to the master cylinder
- Universal design fits virtually all types of master cylinders
- · Automatically maintains the level of new brake fluid in the master cylinder while vacuum bleeding brake and hydraulic clutch systems

PBT70895 **AUTOFILL AUTOMATIC** BRAKE REFILLER · Automatically fills brake fluid reservoir during bleeding

- · Easy to operate retaining clip provides positive clamping to master cylinder reservoir
- No more running reservoir empty
- Saves time and money
- Height adjustment to ensure correct 'Max' level is maintained
- On/off tap
- Eliminates spills onto paintwork · Positive container venting
- to maintain constant fluid flow
- · Manufactured from non-corrosive materials
- 600ml (20.3 Fl oz.) container



EM720C **SMART DIGITAL CLAMP METER**

- Smart automatic detection: No need to select AC or DC volts or resistance. Tester selects the right setting automatically
- Large amp range capability: TRMS AC and DC up to 600A

V HH Ω

Cat IV 600V

EM112-1 **DIGITAL MULTIMETER PROBE SET**

- · Check electric line, immediately find faulty connections
- DC measure up to 49V for all the automotive measures
- Line test-Detects faulty connections in electric circuits
- PWM / MLI signal detector automatically indicates when measuring a square signal used to command idle
- actuator, turbo wastage, EGR, and Canister valve • Measure resistance up to 40 $M\Omega$ when testing ignition
- coil, most of sensors · Continuity signal alarm when testing lamps,
- fuse, connector, and switches



EM121

AC/DC LOW **CURRENT AMP PROBE**

- Measures current from 5 mA to 30A
- · No need to open the circuit, no need for electric contact
- For AC and DC current
- · Can be used with all DMM
- including AC/DC mV function · Measures the current leak
- on vehicle
- For all diagnostic specialist

EM111 AC/DC LARGE RANGE

- **CURRENT AMP PROBE** · Measures current from 20A to 1500A
- No need to open the circuit, no need for electric contact
- · For AC and DC current
- · For automotive and industrial maintenance
- · Able to check engine cranking current or
- charging current on light vehicle and truck

290

TOOLS



- · Can be used with all DMMs

ET3051D **NOID LIGHT TEST KIT**

- Detects whether the EFI system or idle air control are possible faults on no-start vehicles
- Once you disconnect the fuel injectors, plug in a noid light, and crank the engine, a flashing light indicates normal pulsing voltage
- Applications: GM[®] PFI, Ford[®] TBI, Geo[®] TBI, Bosch[®] PFI, GM[®] TBI, GM[®] SCPI, and now new applications of Bosch[®] 2 and Multec[®] with red and green LEDs

INCLUDES:

- Harness extension
- · Blow-moulded case

| PRODUCT # | DESCRIPTION | SET |
|------------|-----------------------------|-----|
| ET3051D | Noid Light Test Kit | |
| ET3055D-3 | Geo® TBI Noid Light | • |
| ET3055D-4 | GM® TBI Noid Light | • |
| ET3055D-5 | SM SCPI | • |
| ET3055D-6 | GM [®] Multitech 2 | • |
| ET3055D-7 | Bosch® PFI Noid Light | • |
| ET3055D-8 | Bosch® 2 Noid Light | • |
| ET3055D-9 | GM [®] PFI | • |
| ET3055D-10 | Ford® TBI Noid Light | • |





ET348X **INTEGRATED TEST LIGHT / VOLTMETER**

- · Interchangeable probe circuit tester with an easy-to-read back lit LCD that displays voltage reading (3-48V range)
- · Equipped with a wide assortment of probes, slip-on adapters, and clips, this tool makes it easy to access even the hardest-to-reach areas of today's vehicles

INCLUDES:

- 1 x 12' High Visibility Retracting Ground Lead
- 2 x Interchangeable Probes
- 1 x Handle with LCD Voltage Display Unit
- 1 x Blow-Moulded Case (Not Shown)

ET64970 PARASITIC DRAW TESTER

Replaceable in-line fuses protect both the meter and tester in the event a high current source on the vehicle is left on.

The multimeter is bypassed with the switch during connection in case of a power surge. The tester and meter can remain connected until other computer systems shut down, isolating the drain. As a convenience, stacking banana connectors are used on the tester. This allows voltage to be measured on various locations on the vehicle during the drain test, using standard test leads.

ET28830 **DIGITAL CIRCUIT TESTER**

- Heavy-duty circuit tester with digital LCD display to accurately show DC voltage
- Two LEDs provide 360° visibility of polarity: red light indicates positive polarity,
- green indicates negative polarity 12' coiled cord
- · Heavy-duty alligator clamp for secure connections

ET115X

- · Probe is insulated to reduce the possibility of short-circuit with other components Computer safe
- · Will not damage sensitive electronic components
- · Operating range 3-49 volts DC to work on most vehicle electrical systems



12V HEAVY-DUTY REMOTE

DIAGNOSTICS

CIRCUIT AND FUSE TESTERS

STARTER SWITCH · Allows technician to remotely engage

- starter while under the vehicle or looking over engine bay Red light glows when the starter switch
- is connected to a hot circuit • 5' (1.5m) Leads
- · Safety shield around leads to prevent electric shock to user

- ET76562 COIL-ON-PLUG (COP) QUICK PROBE VS
- · Easily and quickly determine if a COP is producing a proper spark for the plug
- Eliminates the need for back-probing coil wires and disassembly to test at the coil connector or spark plug
- · Variable sensitivity (VS) for greater diagnostic accuracy and expanded application coverage



12/24V HOOK TIP CIRCUIT TESTER

- Clear moulded handle Requires just one hand to test circuits in hard-to-reach areas
- Has 16-gauge, 44" ground wire with 50 Amp clamp
- Use for circuits, connections, fuses, and 2-cycle engine timing



- · Threaded probe enables use of other screw-on
- · 15' High visibility cord lead

ST380 **SPARK TESTER**

- Tests spark plugs, spark plug wires, and coils without puncturing the wire
- With engine running, place the grooved end of the tool over the plug wire
- · The bulb will flash to indicate spark

ST400 INLINE SPARK TESTER

- · Visually check the ignition system · Connect the tool between the
- spark plug and the plug wire
- Double-ended to offer a straight
- boot and a 90° boot on one tool
- · With the engine running, the tool flashes
- a mirror image of ignition spark

ET112X 6/12/24V CIRCUIT TESTER

TOOLS

- Two-colour LED circuit tester for 6/12/24V systems · Heavy-duty coil extends to 12'
- · Clear moulded handle with stainless steel probe · Permanently attached wire and spring strain relief in

 Circuit board comes with two LEDs: one red LED to verify the tool is hooked up correctly and the other that lights either red or green to indicate a voltage or ground connection

· LED circuit board and lead set are field replaceable

- Small, ergonomic design
- · High intensity bulb
- · Needle-sharp, stainless steel threaded probe

type accessories

292

ET111X

6/12V CIRCUIT TESTER

· Circuit tester for 6V and 12V systems

· Clear handle with stainless steel probe

· Screw-on end cap for easy bulb replacement

· Heavy-duty coil cord extends to 12'

specially hardened moulded

18-Gauge clip with insulating boot







ET72 AMP HOUND 2

- · Measure automotive amperage instantly without removing the fuses
- Audible tone lets you know when you have connection with a fuse and if there is current present in the circuit
- Snapshot Mode and Tracking Mode allow component testing and parasitic drain location
- · Special fuse adapters lock on to fuse and provide hands-free control

FIP76462 UNIVERSAL EFI QUICK PROBE

- · Quickly determine if a fuel injector is firing by detecting a mechanical vibration, such as a fuel injector's pintle movement
- · Works on gas and diesel engines
- · No hunting for injector wires to test at the connector or injector removal required
- The probe is specifically designed to detect the vibrations emitted when the injector fires



MSC28 **AUTO MEMORY SAVER**

- · Prevents the loss of electronic memory
- when disconnecting the vehicle's battery
- · High visibility coiled cord stretches to 8'
- Easy storage in tool box
- OBD II connection uses positive and ground pins only, will not interfere with fault codes
- Coiled cord prevents tangles



ET95902 **CUSTOM AUTO TEST LEAD KIT** · An assortment of the most common leads. probes, and clips INCLUDES: • 1 x 20-Amp Insulated 48" Silicone 4mm Lead Assembly (Red) • 1 x 20-Amp Insulated 48" Silicone 4mm Lead Assembly (Black) • 1 x Short Steel Tipped Probe (Red) 1 x Short Steel Tipped Probe (Black) • 1 x Cable Piercer (Black)

ET95924

INSULATION PIERCING TEST LEAD / PLUG

- Cords stretch to 48" long
- Nickel-plated brass body, nickel-plated phosphor bronze springs, plastic handles, and solderless assembly
- Nickel-silver hook contact is spring-loaded for strong clamp-on action

ET95961 **SUPER-DUTY TEST LEADS**

- Cords stretch to 48" long
- · Copper-plated test clips with heavy-duty insulated boots



ET95959 **HI-VISIBILITY COIL CORD LEAD**

- · Coiled cords stretch to over 60" long
- · Insulated alligator clips on both ends



ET96471 **48" SILICONE TEST LEADS**

· 3.8mm outside diameter leads are rated to maximum 1,000V/10 Amp

ET96471-01 48" SILICONE TEST LEAD - RED

ET96471-02 **48" SILICONE TEST LEAD - BLACK**



DIAGNOSTICS TEST LEADS AND ACCESSORIES

ET96470

2 PIECE INSULATED CROCODILE CLIP SET

- · Fully insulated jaws
- · Maximum voltage/amperage: 1,000V/32 Amp
- · Wide opening jaws
- Connection type is 0.16" (4mm) female banana plug

INCLUDES:

- 1 x Red crocodile clip
- 1 x Black crocodile clip

ET96466 **RIGHT ANGLE BACK PROBES**

- Unique right angle back probe design enables connectivity in confined areas
- · High-flex silicone wire for superior heat and chemical resistance
- · Modular design is compatible with any industry standard
- 4mm shrouded banana plug test lead

ET96473

AUTO BACK PROBING CONNECT KIT

- · Compliments any standard multimeter by adding insulation-piercing and 90° back probe leads
- · Piercers are 3-1/8" in length
- Short back probe wires
- are 11-1/2" long
- · Long test leads are 52" long

INCLUDES:

- 2 x Insulation-Piercing Test Lead Clips
- 2 x Right Angle Back Probe Test
- Lead Clips
- 2 x Silicone Test Leads

ET96468 **OEM MODULAR**

TEST PROBE SET

- · Sharp steel points
- · Maximum voltage/amperage: 1,000V/10 Amp
- · Connection type is 0.16"
- (4mm) female banana plug







ET96470-01 **INSULATED CROCODILE CLIP - RED**

ET96470-02 **INSULATED CROCODILE CLIP - BLACK**

ET96469 **BACK PROBES**

- · Flexible and formable 3/4" pin provides an easy connection past weather pack seals to connector conductors
- Tested to 60V DC
- · Connection type is 0.16" (4mm) female banana plug



ET95916 **CABLE PIERCERS**

INCLUDES: · Cable Piercer (Red) Cable Piercer (Black)



DIAGNOSTICS TEST LEADS AND ACCESSORIES

ET96467 MINI CABLE PIERCERS

- Quick and reliable access
- For cables ø1.0 2.5mm
- · Standard 4mm socket to rear
- Recommended for safe voltage piercing only (600V maximum)

INCLUDES:

ET95923

INCLUDES:

EASY ACCESS

BACK PROBES

· Perfect for connecting to fuel injectors, MAP, and TPS sensors • Impervious to extreme temperatures and automotive solvents

• 2 x 1/32" Back Probe Pins (Yellow)

• 2 x 1/32" Back Probe Pins (Green)

• 2 x 1/32" Back Probe Pins (Red) • 2 x 1/32" Back Probe Pins (Blue)

- Mini Cable Piercer (Red)
- Mini Cable Piercer (Blue)
- Mini Cable Piercer (Green)
- Mini Cable Piercer (Yellow)

ET96467-01

MINI CABLE PIERCER PROBE- RED

ET96467-02 **MINI CABLE PIERCER PROBE - YELLOW**



RTL1176A

7 PIECE 15' RETRACTABLE TEST LEAD SET WITH BANANA PLUGS

- · Used for testing electrical circuits
- Retractable leads extend and lock at a desired length
- · Rewind test lead into its own protective case when not in use
- Features insulated alligator clips



ET95913

EASY ACCESS 76" **BACK PROBE KIT**

• Back probe pins 0.028" / 7mm OD • Extra-long, 76" double-insulated silicone test leads (rated 1000V CAT III, 20 Amp)

INCLUDES:

- 1 x Extra Long Test Lead (Green)
- 1 x Extra Long Test Lead (Yellow)
- 2 x Back Probe Pins (Yellow)
- 2 x Back Probe Pins (Green)

DIAGNOSTICS

TEST LEADS AND ACCESSORIES

ET96041 **UNIVERSAL MAGNETIC GROUND LUG**

- Stop searching for a good place to clip your test equipment ground leads
- · Attaches to any metal surface



ET95911 **SIGNAL BACK PROBE PIN**

· Insulating collar to help eliminate grounding

INCLUDES: 4 x Back Probe Pins (Yellow)

PPRLS01Z **POWER PROBE® LEAD SET**

- High current 10-gauge multi-strand leads

- · Large and small probes can pierce



EASY ACCESS 76"

BACK PROBE KIT FOR SCOPE

- Back probe pins 0.028" / 7mm OD
- Extra-long, 76" double-insulated silicone test leads (rated 1000V CAT III, 20 Amp)

INCLUDES:

- Extra Long Test Lead (Green)
- Extra Long Test Lead (Yellow)
- Extra Long Test Lead (Blue)
- Extra Long Test Lead (Red) Back Probe Pins (Yellow)
- Back Probe Pins (Green)
- 1/32" Back Probe Pins (Blue).
- 1/32" Back Probe Pins (Red)



- and gold-plated electrical connectors
- The super flexible leads come in lengths of 1', 3', and 6' and are stackable, giving
- the technician greater flexibility
- and centre wires from 28- to 8-gauge









ET6100 **FUSE BLOCK CONNECTORS**

- · Fits all Maxi, ATO, and mini size automotive blade style fuse block connectors
- Plated contacts for extra conductivity and durability
- Connector tabs fit 1/4" female quick connects or standard alligator clips



FS21250 FINGER SAVER WIRE **PIERCING GUIDE**

- Quickly, easily, and safely guides the pick point of any circuit tester into centre of all primary automotive electrical wire
- · Holds circuit tester in position allowing work with both hands free
- · Impervious to gasoline, oil, thinners, and other shop chemicals
- · Stores on ground wire of circuit tester



MAL ST115

SUPER TORCH SOLDERING TOOL

- Waterproof piezo automatic ignition Uses standard butane fuel – capacity
- for up to two hours of use
- Long life catalytic tips
- Power Range: 30W 100W

APPLICATIONS:

- · Automotive, truck and aviation repair
- Install heat shrink tubing
- Solder circuit boards
- · Loosen rusted nuts and bolts
- · Can also be used as a torch with a flame of 2,400°F

L55000 MAGNETIC SOLDERING CLAMP

- · Offers an extra pair of hands when soldering
- · Alligator clamps firmly hold wire and small parts when soldering Flexible design allows different ways to
- attach and hold wire

Clips and base are magnetic and can be attached to any ferrous surface Magnetic arms are detatchable and can be moved and used without the base · Base is also hex shaped and can fit in a

vice when needed

OWER PROBE 10 M 8

PPSK


POWER PROBE SOLDERING IRON KIT

- Max Flame Temperature: 930 ° F
- Adjustable Flame Length: .5" 1.25"
- · Butane Fuel Type with electronic igniter
- Organized Durable Case
- · Accessories Tips and Attachments Included

ST230

- Automatic piezo ignition

- Up to four hours use on each filling
- Drop-resistant housing
- · Larger, easy-to-use controls
- Use at any angle with
- hands-free base



RTJ103A MASTER RELAY AND FUSED CIRCUIT TEST KIT

DIAGNOSTICS

RELAY SERVICE KITS

- Jumpers have tabs for clamping and flat pads to place test leads on
- · No need to pierce wires or
- connect multiple jumper wires
- · Easily and securely connect relay test jumpers to a multimeter
- Terminal Leads with Switch/Fuse/ Power provides the technician several ways to check the fuses that are in the panel · Five wire set that fits these
- fuses; Female-Pal, JK, LJK, Male-L-mini, Mini, ATO, and Maxi
- One set of wires has no ends, allowing the technician to crimp any style they need
- · Different sized ends on the wires give flexibility to plug directly in the relay base or to fit other relay sizes not covered by the jumpers
- · Remove any fuse and plug in the correct wire and plug the other end into a meter and take a current reading without using a clamp-on tester · Use the on/off switch to control
- a circuit
- · Test before or after the switch by using the stacking banana plugs
- · The power lead can apply external power to only the circuit that you are working on
- There are two 3-1/2' extensions to be used if you are controlling a circuit while the vehicle is on a hoist
- · The in-line fuse holder (common ATO fuse style) protects the
- circuit and meter when testing · Relay Puller Pliers for removing
- electrical relays on most domestic and import vehicles
- · Offset handle and thin tips allow access to relays in confined areas
- Specially designed tips are angled to
- fit slots or the edge of the relay cover · Allows the relay to pop free from the socket with less chance of damaging
- the relay cover



ST150B 9 PIECE SUPER TORCH SOLDERING KIT

- Patented LEC removable/refillable fuel cell
- LEC filter system eliminates clogging
- · Improved nozzle assembly for sure ignition
- · Ready-to-use in fifteen seconds
- · Integrated hands-free stand
- Uses standard butane fuel
- Can double as a torch with a 2,400°F flame
- Power Range: 30W 125W

INCLUDES

- · Chisel tip Heat shield
- Sponge
- Solder coil






PRO SUPER TORCH

2,500°F Adjustable flame

- · Precise flame adjustment
- · Dual fuel and air controls







ET9037 **RELAY BYPASS SET II**

- · Provides direct control over relay circuit
- Verify load
- · Isolate electrical components
- Plugs in place of relay
- · Provides manual control of circuit
- · Helps identify bad relays, control switches, open circuits, electrical equipment, and power feed
- Operating range: 20-amp continuous, 30-amp surge (12V)

ET9036 **3 PIECE RELAY BYPASS KIT**

- Provides direct control over a relay circuit to operate components within the circuit with the push of a switch
- Easy-to-use, the relay bypass switches are not pole sensitive making them a plugand-play solution
- · Commonly used on circuits for fuel pumps and fan motors, the relay bypass switch allows the technician to isolate electrical components to troubleshoot circuit failure
- · Plugs in place of relay
- · Provides manual control of circuit
- · Helps identify bad relays, control switches. open circuits, electrical equipment, and power feed
- · Operating range: 20 Amp continuous, 30 Amp surge (12V)

APPLICATIONS:

- Small spade relay: 2000 and newer model USA, Korean, and Japanese applications
- · Medium spade relay: common relay for applications spanning most makes and models from the late 1970s through 2009

299

· Large spade relay: late model USA and Japanese vehicles





ET9038A **6 PIECE MASTER RELAY BYPASS SWITCH SET** WITH AMP LOOP

- The Relay Bypass Switch with Amp Loop energizes fuel pumps and any 12V relay by powering a DC motor for testing. It also makes DC motor actuation and current monitoring easy. By attaching an Amp Clamp or Lab Scope, you can monitor the current or amperage readings. It allows a technician to judge the health of the DC electric motor to identify if a motor is drawing more current than specified, or if the current load is inconsistent during operation.
- · Control relay circuit independent of "key-on/key-off" systems
- Run all automotive, 12V DC motors with a push of a switch
- Simplifies fuel injection testing
- Use in conjunction with clamp-on Amp Probes and Lab Scopes
- · Operating range: Up to 20 amp continuous, 30 amp surge (12V)
- · Covers most makes and models



ET8005 **FUSE SAVER**

- Chase down short circuits without replacing fuses
- Three resetting colour matching breaker handles: 10, 15, and 20 amps
- · Allows you to move around the vehicle shake-testing wires while looking for shorts
- · Finds short circuits fast

300

No more overheating fuse boxes



ET8017 **FUSE-SAVER MASTER KIT**

- · Provides a fast and safe solution to the old methods of "smoke testing" a short
- Simply attach the desired breaker handle to the 10' cable and install into the fuse box, then begin shaking wiring harnesses, disconnecting electrical equipment, and other methods to find the source of a short circuit or overload condition
- · Allows the technician to move around the vehicle and shake test wires while looking for a short circuit
- Dual-type fuse box connector with 10' cord helps ease installation of radios, CD players, radar detectors, and other accessory equipment
- · Chase down short circuits without replacing blown fuses

INCLUDES:

- 5 x Specific Fuse Type Adapters
- 1 x Blow-Moulded Storage Case





ET8025

4 PIECE TERMINAL AND TRAILER PLUG CLEANER SET

- · For removing corrosion and debris from trailer terminals and common automotive style wire connectors
- · Great for use on trailer tail light assemblies
- Cleans 4-, 5-, 6-, and 7-spade pin trailer sockets (male and female)
- · Extend life of trailer
- sockets and terminals · Ensure better electrical connections
- Resize terminals
- · Auto/industrial/marine/fleet applications Available individually

ET8024

INCLUDES: Male

ET8040A

FLAT TERMINAL **CLEANERS PIVOT**

 Highly-durable and abrasive coatings that clean connections to reduce diagnostic guesswork and increase overall harness life Works for both male and female connectors on flat (spade) pin-type terminals

INCLUDES:

• 3 x Large, Medium, and Small Cleaners for Most Connectors

ET8042 **12 PIECE FEM BULLET CONNECT CLEANERS**

TOOLS





7-ROUND PIN TERMINAL CLEANERS (TRUCK / TRAILER)

· Precision machined cleaning tool for use with 7-round pin commercial trailer connectors Doubles as a pin/socket wear gauge indicating if the connection needs to be tightened or replaced · For male and female connections

· For tail and side marker light assemblies · Maintains continuity and prevents failure · Quickly and precisely cuts away corrosion

· Female 7-Round Pin Terminal Cleaner

· Complete set of tools to clean round pin type electrical terminals commonly used in Cannon, Deutsch, bullet type and general electrical connections

· Includes twelve individual pieces ranging in sizes from .030" -.120"

· Diamond abrasive coating for precise cleaning, sizing and durability.

• 10 sizes with duplicate cleaners in the 0.030" and 0.040" range. Each file is marked or colour-coded for size.

D/AGNOSTIGS TERMINAL REPAIR



TOOLS

TT95970 12 PIECE MINI TERMINAL TOOL SET EXTENDED SHAFT

- Tri-lobal ergonomic handle design
 TPE (Thermal Plastic Elastomer) over-mould ensures firm grip
- Resistant to acid, fluids, and solvents
- Extended length shafts for improved access in restricted spaces
 Chrome-Vanadium steel shaft with
- Chrome-vanadium steel shart with high-polished chrome plated finish
 Application chart included
- inside storage pouch

INCLUDES:

- 12 x Tools for the Disassembly of Terminal Blocks and Harness Connectors for Asian and European Vehicles
 1 x Application Chart Inside Storage Pouch
- I x Application Chart Inside Storage Pouch





TT7750 Wire terminal tool kit

- Set of three terminal tools and handle for removing wires from terminals without damage
- Terminal tools work on conventional, Pack-Con, and Weather-Pack terminals found on many GM vehicles
- New blue terminal tool fits many Ford applications
 The handle slips over the probes
- to protect the technician's hand and provide extra leverage • All terminal tools are available
- individually skin-packed

TT96030 TERMINAL TOOL KIT

- Fits most GM[®] products computer connectors and terminals
- Individually handled for easy access into tight places
- Colour-coded for easy identification

| 1 | | |
|------------|-----------------------------------|------------|
| PRODUCT # | DESCRIPTION | SIZE MM |
| TT96030-01 | Spring-Loaded Tube Terminal Tool | 3.3 x 28.0 |
| TT96030-02 | Square Blade Terminal Tool | 1.4 x 19.0 |
| TT96030-03 | Flat Blade Terminal Tool | 1.5 x 24.8 |
| TT96030-05 | Fork Blade Terminal Tool | 8.0 x 24.0 |
| TT96030-06 | 3/16" x 1" Flat Blade Screwdriver | - |
| TT96030-07 | Tube Terminal Tool | 3.3 x 28.0 |
| TT96030-08 | Tube Terminal Tool | 4.3 x 13.0 |
| TT96030-09 | Tube Terminal Tool | 3.8 x 13.0 |
| TT96030-10 | Tube Terminal Tool | 3.0 x 13.0 |
| TT96030-11 | Flat Twin Blade Terminal Tool | 3 |
| TT96030-12 | Flat Twin Blade Terminal Tool | 1.6 |

TERMINAL REPAIR

TT95886

7 PIECE DEUTSCH TERMINAL TOOL SET

- Provides the ability to remove terminals from connectors without damaging or destroying the connector
- Deutsch connectors are used on numerous vehicle types including: automotive, motorcycles, HD trucks, construction equipment, agricultural equipment, and some outboard engines

DIAGNOSTICS

• Provides coverage for wire gauges between 4-20

| PRODUCT # | DESCRIPTION |
|-------------|---------------------------------|
| TT95886M-01 | 04 Gauge Wire Terminal Tools #F |
| TT95886M-02 | 08 Gauge Wire Terminal Tool #E |
| TT95886M-03 | 12 Gauge Wire Terminal Tools #D |
| TT95886M-04 | 14 Gauge Wire Terminal Tool #C |
| TT95886M-05 | 16 Gauge Wire Terminal Tool #B |
| TT95886M-06 | 20 Gauge Wire Terminal Tool #A |
| TT95886M-07 | Removal Tool #G |

TT95839

23 PIECE UNIVERSAL TERMINAL TOOL SET

- Contains a wide assortment of terminal tools that will cover a large range of vehicle applications and has the ability to service many makes and models of vehicles without the added expense of purchasing additional kits
 Easily removes terminals from electrical connectors
- Eliminates damage to wires or terminal blocks
- Handles designed for extra grip and comfort
- Handles individually marked on the heads for easy identification on application chart









EV9504 Leak Attack™ pro diagnostic Smoke Machine

- Mac Tools[®] Exclusive Design
- Easy Intake Included
- Two year warranty
- Halogen inspection light
- Removable smoke hose
- Positive/negative pressure gauge
- Includes full accessory kit
- Ideal for finding vacuum leaks, EVAP (fuel vapour recovery), exhaust leaks, seals, gaskets, brake vacuum hoses, cooling systems, oil, wind, and water leaks, diaphragms, central locking and much more











95-0082 EASY INTAKE™ EXHAUST BLADDER

- Easy INTAKE[™] is an inflatable block off bladder with a pressurized vapour pass-through that allows technicians to test an entire intake or exhaust system quickly and easily
- Easy INTAKE[™] can be used with any brand of smoke machine or diagnostic leak detector to block-off the system with its inflatable bladder and pressurize the system with vapour through the pass-through to accurately locate leaks and find additional repair jobs
- Easy INTAKE[™] block off bladder conforms to any shape intake / exhaust: square, round, oval, rectangular and even severely angled and hard to reach intake / exhaust systems, while allowing vapour to pass through for fast diagnostics
- Compatible with any smoke machine, Easy INTAKE[™] fits nearly all automobiles and light duty trucks to quickly leak test the integrity of the entire induction system with one simple procedure

SG1100-10

MINI HVLP GRAVITY

- SPRAY GUN
- Great for small area
- repairs and detail work
- Well-balanced and lightweight
 Includes a 150cc cup and aluminium lid
- 1.0mm fluid tip





GOOCC PAINT CUP
 Fits all SG1300 Series



• Large heavy-duty magnet holds your paint gun without having to drill holes in your paint booth





TIN SNIPS

- Treated for strength, toughness, and durability
- Cuts up to 18-gauge cold rolled sheet steel

| PRODUCT # | CUT | CUT [MM] | HANDLE COLOUR | LENGTH | LENGTH [MM] | TYPE |
|-----------|--------|----------|---------------|---------|-------------|----------|
| TS1 | 1-3/8" | 34.9 | Green | 10-1/2" | 266.7 | Right |
| TS2 | 1-3/8" | 34.9 | Red | 10-1/2" | 266.7 | Left |
| TS3 | 1-1/2" | 38.1 | Yellow | 10-1/2" | 266.7 | Straight |



WATERBORNE Compliant HVLP Full-Size gravity Spray guns

- Well-balanced and lightweight
- Comes complete with 600cc
- aluminium cup with lid • Air Inlet - 1/4 NPS male
- All fillet 1/4 NPS
 Fluid Inlet 3/8"
- Fluiu IIIet 3/6
 Inlat air pressure
- Inlet air pressure 29 psi

| PRODUCT # | AIR CONSUMPTION [CFM] | APPLICATIONS | FLUID TIP [MM] |
|-----------|--------------------------|------------------------------------|-------------------|
| SG1300-13 | 6.8 | Base Coat - Clear Coat High Solids | 1.3 |
| SG1300-14 | 6.9 | Clear Coat - Medium Solids | 1.4 |
| SG1300-15 | 6.1 | Single Stage - High Solids Primer | 1.5 |
| SG1300-18 | 6.1 | Acrylic Enamel - High Build Primer | 1.8 |

PAINT & BODY SPRAYING

ACU1

AIR CONTROL UNIT WITH REGULATOR

- · Removes water, oil, and other contaminants and regulates air pressure
- 160 PSI inverted air gauge • 120 CFM capacity air filter
- 50 CFM chrome-plated
- regulator
- Air Inlet: 1/2" NPT
- Air Outlet: 1/4" NPT



SGCK-22 **22 PIECE GUN CLEANING KIT**

· Cleans virtually any spray gun

INCLUDES:

- 4 x Twisted Brushes • 1 x Nylon Exterior Brush
- 1 x 6 Piece Stainless Needle Set with Handle
- 1 x 5 Piece Precision Mini Brush Set
- 1 x 3 Piece Lube Applicator Set with Handle
- 1 x 2 Piece Round Bar and Gun Lube





BFT1316 PAINT DE-NIBBER FILE

- · The ideal tool for drips, runs, and errors in your
- otherwise perfect paint job
- · Hardened file with two faces in an ergonomically designed rubber grip
- · Handle securely holds the mini-file in proper position
- Easily flipped from course to fine
- Course cut side for fast cutting
- · Fine cut side for finishing

SB2D **DOUBLE DENSITY SANDING BLOCK**

· Gray side is soft and pliable for sanding irregular surfaces; black side is stiff for faster sanding on curved surfaces Size: 2-1/2" x 5" x 5/8"



ADJUSTABLE FILE HOLDER

- Top quality file holder for 14" body files
- Turn buckle design permits flexing
- Rotating handle designed for right or left hand use

HAND TOOLS

PAINT & BODY

BTS7F

7 PIECE FIBREGLASS HANDLE AUTO BODY REPAIR TOOL SET

- Drop-forged hardened steel
- Machined and polished work surfaces
- Meets ASME/ANSI standards
- · Hardened steel machined, and polished large round work surface





- BT1036DS Light Dinging Spoon
- BT1058TD Toe Dolly
- BT1059HD Heel Dolly
- BT1060GPD General Purpose Dolly
- Blow-Moulded Case

BTS4F

4 PIECE FIBERGLASS HANDLED HAMMER AUTO BODY **REPAIR TOOL SET**

- Drop-forged hardened steel
- Machined and polished work surfaces
- · Limited lifetime warranty
- Meets ASME/ANSI standards
- · Fiberglass handles with rubber overmould

INCLUDES:

- 2 x Hammers
- 1 x Dolly
- 1 x Spoon



BTH153CCS **CROSS-CHISEL SHRINKING** HAMMER WITH WOOD HANDLE

- Cross-grooved
- Extra wide faces are cross grooved and used for shrinkage on large surfaces chisel end used on sharp corners
- · Hickory handle with lacquer finish, hardened steel machined, and polished large
- round work surface · Weight: 0.9 lbs.

BTH162S WOOD SHRINKING HAMMER

- For work in close quarters
- · Expertly machined serrations
- on the round face
- · Weight: 0.8 lbs.











| PRODUCT # | DESCRIPTION | SET |
|-----------|---|--------|
| BTS7F | 7 Piece Fibreglass Handle Auto Body Repair To | ol Set |
| BT1036DS | Light Dinging Spoon | • |
| BT1058TD | Toe Dolly | • |
| BT1059HD | Heel Dolly | • |
| BT1060GPD | General Purpose Dolly | • |
| BTH153CRF | Fibreglass Handle Curved Chisel Hammer | • |
| BTH164UPF | Fibreglass Handle Utility Pick Hammer | • |
| BTH162SF | Fibreglass Handle Shrinking Hammer | • |



- · Medium-size point and reach
- Low-crown strawberry point for balance
- Drop-forged hardened steel
- · Machined and polished work surfaces
- Meets ASME/ANSI standards
- Weight: 0.9 lbs. · Face radius: 3/32"

BTH153CC - WOOD **BTH153CCF** - FIBREGLASS **CROSS-CHISEL HAMMERS**

- Excellent for finishing
- · Cross-peen used for working in sharp corners, around moulding, and for caulking
- · Weight: 0.9 lbs.



BTH155FBF

FENDER BUMPING HAMMER WITH FIBREGLASS HANDLE

- For bumping where hand and dolly cannot reach
- Ample clearance for obstructions
- Also used as a caulking iron · Weight: 2.8 lbs.



BT1057LTD **LIGHT TOE DOLLY** • Designed for flat surfaces

BMD200 MULTI-DOLLY STANDARD

- Smoothing round face
- Smoothing round curve
- · End curve dolly
- Spoon curve dolly
- · Flat face with bent curve
- Small curve wedge dolly
- · Awl type dolly

BTH170DS - WOOD **BTH170DSF** - FIBREGLASS **DOOR SKIN HAMMERS**

- · For high-crown work and finishing, without poking holes in thin sections
- Weight: 0.9 lbs.

BT1052SD SPOON DOLLY

• Forming and caulking tool for the deep pockets of quarter-panels, rear fenders, and lower trunk panels

WD1250 680KG EASY ROLLER[™] WHEEL **DOLLY POSITIONING SYSTEM**

• Shaped like the BT1057LTD but has

one face covered with raised serrations for shrinking metal stretched by dents

BT1058SD

SHRINKING DOLLY

- · Provides a simple and efficient method of moving a disabled vehicle around a shop
- · Position at each wheel of a vehicle weighing up to 2.72 Ton (6,000 lbs.) and use the foot pedals to activate the hydraulic lift
- · One individual can easily move the car throughout the garage
- · Fits tread widths up to 12" and the four heavy-duty casters support up to 680kg (1,500 lbs.) per unit
- Hydraulic lift mechanism with locking pin
- · Four heavy-duty phenolic casters protect
- shop floors from damage
- Weight: 20kg (44 lbs.)
- · Item sold as one set or individually

HAND TOOLS

BPR6K

PULL ROD SET

- · Eliminates removal of headliners and inner panels
- · A must for the body mechanic

INCLUDES:

- 4 x Pull Rods with Formed Shanks • 2 x Pick Rods with Straight Shanks
- 1 x Stainless Steel Straight Edge • 1 x High-Speed 5/32" Drill Bit

PAINT & BODY

UT300XL-SET

3 PIECE XL TRIM & PANEL CLIP LIFTER SET

- Extra-long to provide more access for hard-to-reach areas
- Robust design for the more stubborn clips
- High-polish, chrome finish protects delicate
- surfaces as well as prevents corrosion
- Rubberised handles for grip and comfort

UT500-SET 5 PIECE TRIM & PANEL CLIP LIFTER SET

- Easily remove clips used to fasten various automotive trim pieces and panels
- Five specifically designed tool configurations provide a wide application range
- High-polish, chrome finish protects delicate
- surfaces as well as prevents corrosion Rubberised handles for grip and comfort



UPT100-SET **5 PIECE PLASTIC MOULDING /**

TRIM REMOVER

- · Great tools for trim work and plastic upholstery fasteners
- · Use with ease and without scratching
- the body panel or interior moulding

UPT101 WIDE MOULDING / TRIM REMOVER

UPT103 NARROW MOULDING / **TRIM REMOVER**


UPT105 CLIP MOULDING / TRIM REMOVER

308









UPT103

MR151 WINDOW BELT **MOULDING REMOVER**

· Quickly removes all window belt mouldings without damage to the window or the moulding

309





| | BTMC-1A 5 PIECE MIGHTY MIDGET DANEL CLAMP • Allows door to be closed to check alignment before welding begins • Actual size only 5/8" wide • Package of five clamps | <section-header></section-header> | HPF100 FLANGER AND PUNCH TOOL (GMM) • Swivel head • Max sheet thickness up to 18-gauge (0.8mm) • Crimp and punch sheet metal (aluminium, copper, or ductile material) | CRIMP WIDTH CRIMP WIDTH PUNCH PUNCH 7/8" 22 15/64" 6 |
|--|---|--|---|--|
| SDGGO1 B PIECE LIGHT COVER REMOVAL SET INCLUDES: 9 SDGGO11 - Removal Tool-Straight 5 SDGGO12 - Removal Tool-Angled | WH6390 WINDOW HOLDER • Holds door glass while working on the window regulator • Works on all cars and trucks with a top door frame | CLESTER CLE | 1 x LOC80A - Universal Easy Jim 1 x LOCLT-95 - Slide Jim 1 x LT100 - Plastic Slip Jim 2 x | |
| BK1200 HEAVY-DUTY 12 LBS. BODY KNOCKER SED With its heavy-duty 12 lbs. hammer and multiple attachments, this body knocker set is ideal for a multitude of pulling applications | | | LT329G NITE GLOW LOCK TOOL KIT INCLUDES: | |
| BF085SA DBS. KNOCKER SET Square hammer with solid steel shaft Square hammer with solid steel shaft Hammer and Shaft Nose Piece Puller and Screw Package Door Edge Tool Nut Package | | | LT32922 - Easy Wedge STK32915 - Big Easy Lockout Rod 32920 - Big Easy Non-Marring Wedge STK32924 - Non-Marring Paint Protector STK32930 - Big Easy Lock Knob Lifter | LT335 2 PIECE EASY ACCESS AND INFLATE-A-WEDGE™ KIT |
| | | | LT271 PLASTIC DOOR WEDGE • Non-marring plastic wedge for use with lockout tools | AND INFLATE-A-WEDGE KIT INCLUDES: • 1 x Plastic Slim Jim • 2 x Plastic Wedges • 1 x Inflate-a-Wedge™ |







LSC4870A **UNIVERSAL SUPPORT** CLAMP T-HANDLE

- Holds gas-charged lift supports found on hoods, tailgates, hatchbacks, and trunks • Aluminium body and brass threads
- prevent damage to the lift support



LT329 **BIG EASY LOCK TOOL**

INCLUDES:

- Heavy-Duty One-Piece 1/4" x 56" Lockout Tool
- Sure Grip Lock Button Lifter
 Large Plastic Door Wedge



LT275 INFLATE-A-WEDGE™

- Durable, inflatable wedge for use with lockout tools or paintless dent removal • Heavy-duty construction with hand pump

PAINT & BODY HAND TOOLS



PS15-KIT **PROFESSIONAL HAND PLIERS RIVET TOOL KIT**

- Robust aluminium casting and vanadium steel handle design
- Setting capacity: aluminium rivets up to 3/16" (4.8 / 5.0mm) body diameter
- · Contoured handle grips for comfort
- · Rivet retaining handle design for one-hand operation
- Supplied with nosepieces for 3/32", 1/8", 5/32", and 3/16" (2.4mm, 3.2mm, 4.0mm, and 4.8mm) rivets Supplied nosepiece wrench

INCLUDES:

- 2 x Nosepieces for 3/32 3/16" (2.4 4.8mm) Rivets
- 2 x Jaws for 3/32 3/16" (2.4 4.8mm)
- 1 x Jaw Pusher Spring for 3/32 3/16" (2.4 4.8mm)
- 200 x Assorted Rivets
- 60 x Back-Up Plates
- 1 x Wrench

PS15

RIVET TOOL

• Lightweight, professional grade PS15 tool

| PRODUCT # | LENGTH | LENGTH [MM] | WEIGHT [KG] | WEIGHT [LBS.] |
|-----------|----------|-------------|-------------|---------------|
| PS15 | 9-13/20" | 245 | 0.6 | 1.3 |

BTC27 **27 PIECE BODY CLIP SET**

- · Perform on a wide variety of trim work and other delicate applications
- · Non-marring impact resistant plastic
- Slim design for work in tight areas



PNT110-M-KIT **METRIC INSERT TOOL KIT**

· Ergonomically designed to fit your hand with contoured grips for comfort

INCLUDES

- 1 x 190 Piece Variety of metric threaded inserts,
- ideal for use in a broad range of applications 4 x Mandrels and nosepieces for sizes:
- M3, M4, M5, and M6

PS45

HEAVY-DUTY LEVER RIVET TOOL

- Setting capacity 6.4mm diameter
- Telescopic levered high-capacity rivet tool
- · Professional standard, heavy-duty steel construction
- Two-position telescopic levers extend to maximize
- leverage and pulling force
- · Non-extended position makes tool more compact • Supplied with nose-pieces for 3.2mm, 4.0mm, 4.8mm,
- and 6.4mm diameter rivets

MAC 524

| | PRODUCT # | LENGTH | LENGTH [MM] | WEIGHT [KG] | WEIGHT [LBS.] |
|---|-----------|--------|-------------|-------------|---------------|
| - | PS45 | 26" | 665 | 2.6 | 5-3/4 |

S240P **DZUS® FASTENER TOOL**

• Designed for DZUS® fasteners which are used on race cars to hold body panels to frame and also used on aircraft engine compartment panels

| OVERALL Length | OVERALL Length [mm] | TIP THICKNESS | TIP WIDTH | |
|-------------------|---------------------------|------------------|-----------|---|
| 6-1/16" | 153.9 | 3/64" | 35/64" | 1 |

PAINT & BODY HAND TOOLS



PRODUCT #

UTS024A

UTSO36A

UT018A

UT026A

UT027A

UT028A

UT029A

UT031A

UTS024A

6 PIECE UPHOLSTERY AND TRIM SET

UTS036A

2 PIECE SMALL UPHOLSTERY TOOL SET

- UT026A "V" notch and UT027A "U" notch
- upholstery tools handle all styles of clips • UT028A "U" notch and UT029A "V" notch
- small trim and tack tools remove trim, moulding, and emblems • UT031A upholstery tucking tool for tucking
- head liners and seat cushions has rounded edges to protect material from damage
- UT018A removes hinged side door panels · Wide blades which are less likely to damage
- painted and upholstered surfaces
- Ergonomic design handles with thumb stop for maximum control

MAC-GRIP[™] UPHOLSTERY TOOL 10"

UT2BB

UT1BB

MAC-GRIP[™] UPHOLSTERY TOOL 20"

- Rubberized Mac-Grip[™] handles provide maximum comfort and grip
- · Properly pulls body clips from body reducing risk of damage to panels and clips

L42480

- · Designed for easy fastener removal while helping
- to prevent damage to fasteners and body panels
- · Angled head for leverage when prying

312



TOOLS









UPHOLSTERY TOOLS

- · Removes a variety of door and body trim fasteners
- Comfort-Grip[™] handle

| PRODUCT # | DEPTH | OPENING WIDTH |
|-----------|-----------------|------------------|
| UT3VA | 9/32" "V" Notch | 3/32" "V" Notch |
| UT4UA | 1/2" "U" Notch | 11/32" "U" Notch |

| DESCRIPTION | S | ET | |
|-------------------------------|---|----|---|
| ece Upholstery and Trim Set | | | |
| ece Small Upholstery Tool Set | | | |
| Reversed Door Panel Tool | | • | |
| Ergo "V" Panel Clip Tool | | • | |
| Ergo "U" Panel Clip Tool | | • | ľ |
| Small Ergo "U" Panel Clip | • | • | |
| Small Ergo "V" Panel Clip | • | • | |
| Upholstery Tucking Tool | | • | |
| | | | |

DESCRIPTIO

6 Piece Upholstery and

2 Piece Small Upholste



- Long reach provides cutting leverage and distance needed in today's long dash windshields
- · Screws that secure the blade are flush mounted to prevent damage to dash and moulding
- · Centred blade can be used from either side
- Uses utility knife blades like 11-921A

PANEL CLIP REMOVAL PLIERS





LT855A **TEXAS TWISTER AIR HAMMER PULLING KIT**

- For use with .401 shank air hammer • One hand operation allows user to hold component so it doesn't fall as it's removed
- 20" extension for access to recessed items • 1/2"-20 connecting bar allows for connection to other standard pulling attachmentspockets of quarter-panels,





C3X 3/8" SPOT WELD CUTTER

- · Double-end blade
- Three per pack

C117X 3/8" SPOT WELD CUTTER • Double-end blade

• 1/4" Arbor with retractable pilot

SWC900 **SPOT WELD CHISEL**

- Separates spot welded panels
- Use to separate panels after
- the spot weld has been drilled out Panels are separated without damage
- The blade is sharpened on three sides and offset for clearance

SPECIALITY TOOLS DRIVE TRAIN



HEAD BOLT SOCKETS

· Designed for head bolts on VW and Audi

| PRODUCT # | DESCRIPTION | SIZE | DRIVE Size | POINT Size | APPLI |
|-----------|------------------------------------|------|---------------|---------------|-------------------|
| SC475B | VW / Audi Polydrive Head Bolt Tool | 10 | 1/2" | 6 | Cylinder head bol |
| SC90 | Spline Head Bolt Socket | 10 | 1/2" | 12 | 10mm head bolt |
| SC91 | Spline Head Bolt Socket | 12 | 1/2" | 12 | 12mm head bolt |

DL200P

4 PIECE 1/2" DRIVE **COMBINATION DRIVELINE** SOCKET SET - 12-PT.

- Great for most limited access fasteners to remove and install: driveline bolts, torque converters, cylinder heads, 4x4 transmission casings
- Universal design provides greater access

DL600P

6 PIECE 1/2" DRIVE **COMBINATION DRIVELINE** SOCKET SET - 12-PT.

- · Great for most limited access fasteners to remove and install: driveline bolts. torque converters, cylinder heads, 4x4 transmission casings
- Universal design provides greater access







SC89 7MM VW[®] / OPEL[®] **TRIPLE SQUARE**

 Drive size: 3/8" · Works on previous generation VW® constant-velocity joints and Opel® manifold bolts

NSM10MM **10MM MAGNETIC NUT SETTER**





SBM70990 **STRETCH BELT MATE**

• Use for all stretch fit belt applications · This universal kit allows for the installation, removal, and reuse of all stretch fit belts



olts on VW and Audi olts on VW and Audi olts on VW and Audi

SPECIALITY TOOLS DRIVE TRAIN



SBT590 RATCHETING SERPENTINE BELT SET

- · Releases tension on serpentine belts with a spring-loaded belt tensioner
- · Ratcheting head with freewheel position allows maximum leverage
- · Set ratcheting head to the middle or neutral/freewheel position and once maximum travel point is reached simply click lever into place to lock the ratchet mechanism Comes with extension for hard-to-reach belt tensioners
- · This tool will work where conventional ratchets or breaker bars won't fit due to limited access

SBT734 SERPENTINE BELT TOOL GRABBER

- Designed to help in the installation and removal of serpentine belts
- · Has a gripping end that provides a positive grip on the serpentine belt, allowing user to access tight and difficult areas
- · Long reach (26-1/2") and comfort handle to make grasping belts easy

L30600 **CV BOOT CLAMP PLIERS**

- · A special boot clamp crimping pliers that
- is designed to work in confined spaces
- The pliers work from the side (head is turned 90°) unlike traditional tools that work from the end

SBT59800

MASTER SERPENTINE BELT SET

- Fits belt tensioners requiring 13mm, 14mm, 15mm, 16mm, 18mm hex, and both 1/2" and 3/8" square drive sizes
- 13mm and 16mm. Sockets are built into the handle
- · Covers most domestic and some import applications

| PRODUCT # | DESCRIPTION | DRIVE SIZE | SIZE [MM] | SI | ET |
|--------------|--------------------------------|------------|-----------|----|----|
| SBT59800 | Master Serpentine Belt Set | | | | |
| SBT590 | Ratcheting Serpentine Belt Set | | | | |
| SBT57400-450 | Replacement Socket | - | 18 | • | • |
| LIS57580 | Replacement Socket | - | 16 | • | • |
| SBT57400-440 | Replacement Socket | - | 15 | • | • |
| LIS57390 | Replacement Socket | - | 14 | • | • |
| SBT57400-500 | Replacement Socket | - | 13 | • | • |
| SBT57560 | Square Drive Socket | 1/2" | - | • | • |
| SBT57400-530 | Square Drive Socket | 3/8" | - | • | • |
| LIS59100 | Short Extension Bar | - | - | • | • |
| LIS59140 | Adapter | - | 19 | • | • |
| SBT590-3 | Ratcheting Handle with Grip | - | _ | • | |
| LIS59780 | Handle with Grip | - | - | | • |

SBT8586 RATCHETING

SERPENTINE BELT TOOL

• 15mm x 3/8" Male Square,

16mm x 1/2" Male Square



SBT8585 (NOT SHOWN)

RATCHETING SERPENTINE BELT TOOL

• 13mm x 14mm, 18mm x 1/2" Male Square

SBT8591 (NOT SHOWN) RATCHETING SERPENTINE BELT TOOL

• 14mm x 17mm, 19mm x 3/4" Male Square

CF62B PRE-SET **CYLINDER DEGLAZER**

(50.8 to 177.8mm)

4" (101.6mm)

PRC144 PISTON RING **COMPRESSOR SET**

· Fine tooth ratcheting lock permits bands to be contracted in extremely small increments

DRIVE TRAIN

· Set components are also available individually along with six additional bands. 4-3/8" through 5-5/8"

| DESCRIPTION | OVERALL LENGTH [IN] | SET |
|---------------------------|--|---|
| Piston Ring Compres | sor Set | |
| Ring Compressor Pliers | _ | • |
| Piston Ring Bands | 3-3/8" - 3-5/8" | • |
| Piston Ring Bands | 3-5/8" - 3-7/8" | • |
| Piston Ring Bands | 3-7/8" - 4-1/8" | • |
| Piston Ring Bands | 4-1/8" - 4-3/8" | • |
| F | Piston Ring Compress Ring Compressor Pliers Piston Ring Bands Piston Ring Bands Piston Ring Bands | DESCRIPTION [IN] Viston Ring Compressor Set Ring Compressor Pliers - Piston Ring Bands 3-3/8" - 3-5/8" Piston Ring Bands 3-5/8" - 3-7/8" Piston Ring Bands 3-7/8" - 4-1/8" |



C

SPECIALITY TOOLS

BRD129MA

RACE BEARING AND

· Nine discs for most popular

SEAL DRIVER SET

bearing sizes

Comes in a sturdy

blow-moulded case

BD3142MA 22 PIECE BUSHING REMOVER AND INSERT KIT

- Sizes from 3/8" x 7/16"
- through 1-1/4" x 1-3/8" Three drivers and nuts for drivers
- Blow moulded case



• Capacity: 2" to 7" · Medium grit stones:

316







VC572 LARGE VALVE SPRING COMPRESSOR

- · Designed to compress valve springs on overhead valve engines
- Includes two valve spring adapters, which fit valve spring
- retainers up to 1" (25mm) and 1-3/16" (30mm)
- · Direct action compressor lever gives better visibility of valve spring retainers located in difficult access areas

| JAW OPENING IN. / MM | THROAT HEIGHT IN. / MM |
|----------------------------------|------------------------|
| 1-3/8" to 5-5/8" / 34.9 to 142.9 | 5-7/8" / 149.2 |
| | 1. N. 1997 (1997) |
| | |



BC120200 **MAGNETIC BEARING CUP INSTALLER**

- · Installs bearing cups with the assistance of an internal magnet
- Designed to be used for many automotive and light truck driveline applications

FT131108 LARGE MASTER BEARING **RACE DRIVER**

• All-in-one design, eliminating the need for a driver and several different heads

Three-step jaw accommodates sizes;

18-56 mm (0.75" – 2.25") range with a 10mm depth/reach 39-77 mm (1.5" – 3.0") range with a 10mm depth/reach 48 - 86mm (2.0" - 3.5") range with a 20mm depth/reach · Can be used on most vehicles, including motorcycles



BD3143MA 9 PIECE HEAVY-DUTY BUSHING REMOVER AND INSERT KIT

- Sizes from 1-5/16" x 1-7/16" through 1-3/4" x 1-7/8"
- · Blow moulded case



CA528

17 PIECE CLUTCH ALIGNMENT TOOL SET

- Works on virtually all cars and light-duty trucks
- · Aligns clutch plate properly by using tapered cones and pilot adapters
- Compatible with both metric and SAE sizes

INCLUDES:

| SAE: | METRIC: | | |
|----------------------|--|-----------|---------|
| • 7 x Pilot Adapters | 5 x Pilot Adapters | • 1 x 3.5 | omm Pin |
| • 1 x Clutch Disc | • 2 x Clutch Disc | • 1 x 4 n | ım Pin |
| Centring Adapter | Centring Adapters | • 1x4.5 | omm Pin |

• 1 x 6mm Pin • 1 x 7mm Pin • 1 x 10mm Pin 1 x Alignment Shaft
 1 x Alignment Shaft
 1 x 5mm Pin



OFH245C ADJUSTABLE OIL FILTER PLIERS

- · Covers filters from 2" to 4-1/4" diameter
- Three contact points
- Made of forged alloy steel with heavy-duty textured grips

OFHPSETA AUTO AND TRUCK FILTER PLIERS SET

· Heavy-duty forged jaws with sharp teeth that grip the most stubborn oil filters • Two new sizes that cover filters from 2-1/4" to 7" diameter

| PRODUCT # | DESCRIPTION | SIZE | SET |
|-----------|---------------------------------|-------------------------|-----|
| OFHPSETA | Auto and Truck Filter | Pliers Set | |
| OFH287A | Auto and Truck Filter Pliers | 3-3/4" to 7" 18" | • |
| OFH297A | Auto and Truck Filter Pliers | 2-1/4" to 5" 13-1/2" | • |

L63600 **OIL FILTER WRENCH**

FROM 2-1/2" TO 3-1/8"

- · The large range enables this wrench to fit most standard size filters
- Works great in tight spots since it works from the top of the filter
- Use with 3/8" drive ratchet or breaker bar



OFH276B 3-PRONG HEAVY-DUTY FILTER WRENCH

· Gear-driven hardened metal legs grip and turn the tightest filters • Use with 1/2" square drive tools • Filter diameter: 2-1/2" to 4" (63.5 to 101.6mm)





- Compact for access into tight areas
- High torque capability
- No damage to filter when loosening or tightening
- Automatic one hand adjustment on filters
- · Wrench stays in position on filter while searching for a ratchet
- · Patented grip system
- Size Range: 60-80NM





OFKIT5PC **5 PIECE OIL FILTER CUP WRENCH SET**

- Filter cup wrenches will service 98% of the cars sold in the USA
- Made of super-strong nylon fibre composite that will withstand more torque than conventional metal filter wrenches
- · Metal insert in wrench for strength



OF4B **OIL FILTER WRENCH KIT**

· Features one handle and yoke assembly with four different bands

| PRODUCT # | DESCRIPTION | FILTER SIZE | SET |
|-----------|-----------------------|------------------|-----|
| OF4B | Oil Filter Wrench Kit | | |
| OF4B-01 | Handle and Swivel | _ | • |
| 0F4B-02 | Pin | - | • |
| OF4B-03 | Oil Filter Band | 2-3/8" - 2-3/4" | • |
| OF4B-04 | Oil Filter Band | 2-7/8" - 3-1/4" | • |
| OF4B-05 | Oil Filter Band | 3-1/2" - 3-7/8" | ٠ |
| OF4B-06 | Oil Filter Band | 4-1/8" - 4-7/16" | • |







OFS7-SET 7 PIECE FILTER SOCKET SET

| PRODUCT # | SIZE In. / Mm | APPLICATIONS | SET |
|-----------|------------------|--|-----|
| OFS7-SET | 7 Piece Filter | Socket Set | |
| LIS13280 | / 25 | Fleetguard® filter on motor homes, buses, and some medium-size trucks with Cummins® engines. Also some K&N® filters | • |
| LIS13290 | / 28 | '10 - '18 Dodge [®] Cummins [®] 6.7L fuel filter | ٠ |
| LIS14600 | 1-1/8" / 29 | Dodge [®] Cummins [®] fuel filter | ٠ |
| LIS13310 | / 24 | Cadillac [®] and some BMW [®] | ٠ |
| LIS13320 | / 27 | '03 and later $\rm Mercedes^{\circledast}$ 1.8L, Smart and some $\rm VW^{\circledast}$ | ٠ |
| OFS145 | / 35/36 | Ford® 6.0L Diesel fuel and oil filter housings, Mini Cooper® and BMW® oil filter housings, Mack® Truck oil filter housing | • |
| OFS147 | 1-1/4" / 32 | GM® Ecotec 2.0L, 2.2L, 2.4L 4-cylinder oil filter housing, Chevrolet [®] HHR 2.4L oil filter housing and some Saturn [®] and SAAB [®] | ٠ |



HEAVY-DUTY OIL FILTER WRENCHES

• Use with 1/2" square drive ratchet or breaker bar

| PRODUCT # | APPLICATIONS | FILTER SIZE |
|-----------|---------------------------|--------------------|
| OFH2320B | Full Size Trucks and Vans | 4-1/8" - 4-21/32" |
| OFH2321B | Full Size Trucks and Vans | 4-21/32" - 5-5/32" |
| OFH2322B | HD Equipment | 5-5/32" - 5-21/32" |







SWIVEL OIL FILTER WRENCHES

· Stainless steel band with projection welds for strength and anti-corrosion Heat-treated handle/alloy steel swivel with increased metal thickness

| PRODUCT # | APPLICATIONS | FILTER SIZE |
|-----------|---------------------------|------------------|
| 0F537A | Compacts and Imports | 2-7/8" - 3-1/4" |
| OF535A | Standard Size Oil Filters | 3-7/16" - 3-3/4" |

BH14550

5 PIECE BREATHER HOSE RELEASE TOOL SET

- Designed for European vehicles that utilize plastic hose locks in the engine, which can easily be damaged if removed improperly · Lightweight aluminum anodized
- · Compact size and slim design allow for easy installation and removal of the fittings, saving the technician time · Applications include Audi, BMW, Volkswagen, Mini and Mercedes Benz vehicles

OFH635 BELT FILTER WRENCH

 Use with 1/2" drive ratchet or breaker bar to remove filters up to 6-1/2" Strong nylon belt will not slip

OF989

TRUCK SWIVEL OIL FILTER WRENCH

• Fits filters 4-5/16" to 4-3/4" and Cummins[®] and Detroit Diesel[®] engines



OF991 TRUCK SWIVEL OIL FILTER WRENCH

• Fits filters 5-1/4" to 5-3/4" and Caterpillar® engines



L60200 **HEAVY-DUTY STRAP WRENCH**

- · A heavy-duty, heat-treated alloy steel
- yoke and strong web strap • Use with 1/2" drive ratchet or breaker
- bar to remove filters up to 6-1/2".
- 3-5/8" Long yoke fits into tight areas

LD11102 **8-GALLON OIL LIFT DRAIN**

- · Quick-release lock ring for fast raising and lowering of upper tube with a total adjustment range of 22-1/2"
- Large 15" funnel with strainer
- · Heavy-duty clamp with height
- · Specially shaped jug
- not warp with hot oil · Large handles make
- Big pour spout with
- wheels swivel and roll easily

SP57HB **SEAL PULLER WITH COMFORT-GRIP[™] HANDLE** • Two-sized tips to fit most seal applications

OFPKIT4PC 4-PC. PLASTIC OIL PAN PLUG TOOL KIT

- · Contains tool and adapters to remove plastic oil pan drain plugs found on many late model Ford[®], Volkswagen[®], Audi[®] and BMW[®] vehicles
- Includes adapters for Ford/Lincoln plastic oil pan drain plugs of engines: 2.7L, 2.7L (2018), 3.0L, 3.3L, 3.5L Turbo from 9-12-2018, 5.0L (2018)
- The adapters will not damage drain plugs and are designed to slot in and easily release these plugs
- · Comes in a hard case for easy storage





- adjustment range of 15"
- · Reinforced base will
- Four 2-1/2" ball bearing
- holds 8 gallons
- pouring easy
- threaded cap





S120P **SEAL PULLER**

- A few hammer taps on tool back removes seals on automatic transmissions
- Standard 1/2" stock

SF19802 **2 PIECE SUPER FUNNEL**

- Use the large end to fill the crank case and the antifreeze receptacle without dripping on the engine cover or paint job
- · Use as a long super funnel with both parts screwed together





SP700A **30° BEND SPARK PLUG BOOT PULLERS**

SPKM12-SET **12 PIECE METRIC**

SPARK PLUG SOCKET SET

SP600A (NOT SHOWN) **70° BEND SPARK** PLUG BOOT PULLERS

• Allows for easier access to the boot

· Custom handle making it easier to grip





- Plug starter is intended to be used to start spark plugs in difficult to reach areas · This tool consists of flexible beads (12-1/2" long overall) with a twist handle
- on one end and a spark plug holder on the other



STARTER

- · Flexible, sure grip • Universal size, fits all spark plugs
 - · Durable, convenient, and non-marring

UNIVERSAL SPARK PLUG SOCKET 3/8" DRIVE

- · Rubber retainer holds the spark plug by the porcelain
- insulator for better grip
- · Highly chromed finish for easy clean up and long lasting corrosion protection • Knurled end for easy turning by hand
- · May be used with or without an extension

| PRODUCT # | SIZE | DESCRIPTION | TYPE | CHROME |
|-----------|------|-----------------------------|-------|--------|
| SC179RA | 5/8" | Universal Spark Plug Socket | Block | • |
| SC181R | 5/8" | Universal Spark Plug Socket | Ball | |
| SCU14MMR | 14mm | Universal Spark Plug Socket | Block | • |

THIN-WALL SPARK PLUG SOCKETS

· Thin-wall design ideal for spark plug wells with limited space

SC177

Rubber insert grips spark plug securely

IGNITION

- · Hex end allows the use of a wrench if necessary
- High polish chrome-plated finish for long lasting corrosion resistance

| PRODUCT # | SIZE | OVERALL Length | OUTSIDE DIA |
|------------|---|-------------------|-------------|
| SC177RTW | Thin-Wall Spark Plug Socket 16mm | 2-1/2" | 25/32" |
| SC214MMRTW | Thin-Wall Spark Plug Socket 14mm - 12-PT. | 2-3/4" | 23/32" |

SPECIALITY TOOLS

SC178R

SC178R 13/16" SPARK PLUG

SOCKET

SC177R 5/8" SPARK PLUG




- · Rubber retainer holds plug by the
- porcelain insulator for better grip
- Knurled for firm control
- Hex end allows turning by wrench
- Chrome plated • 3/8" Drive



SPK9-SET

9 PIECE MULTI-LENGTH SPARK PLUG SOCKET SET

- Three different sizes and three different configurations most commonly used when working with spark plugs: 9/16", 5/8",
- and 13/16" sizes in standard, universal, and extra deep styles Highly chromed finish for easy clean up and
- long lasting corrosion protection
- · Each socket is knurled for easy turning by hand









MAGNETIC SPARK PLUG SOCKET INSERTS

- · Magnet firmly holds both the insert in the socket, and the spark plug in the insert
- · Helps prevent damage to the ceramic portion of the spark plug
- Four sizes fit most domestic and imported spark plug sockets

| PRODUCT # | SIZE | MAC TOOLS SOCKETS SERVICED |
|-----------|-------|---------------------------------|
| SP530 | 0.54 | SC177R, SC179RA |
| SP531 | 0.58 | SC163R, SC169R, SC181R |
| SP532 | 0.7 | SC163R, SC169R, SC181R |
| SP533 | 0.785 | SC164R, SC178R, SC180RA, SC182R |

3/8" DRIVE DEEP SPARK PLUG SOCKETS

| PRODUCT # | SIZE |
|-----------|--|
| SC10MMR | 3/8" Drive Deep Spark Plug Socket 10mm |
| SC16MMR | 3/8" Drive Deep Spark Plug Socket 16mm |
| SC18MMR | 3/8" Drive Deep Spark Plug Socket 18mm |
| SC21MMR | 3/8" Drive Deep Spark Plug Socket 21mm |
| SCD16MMRD | 3/8" Drive Extra Deep Spark Plug Socket 16mm |
| SCD21MMRD | 3/8" Drive Extra Deep Spark Plug Socket 21mm |
| SCU16MMR | 3/8" Drive Deep Universal Spark Plug Socket 16mm |
| SCU21MMR | 3/8" Drive Deep Universal Spark Plug Socket 21mm |

| PRODUCT # | SIZE | OVERALL Length | OUTSIDE DIA | SET |
|-----------|--|-------------------|----------------|-----|
| SPK9-SET | 9 Piece Multi-Length Spark Plug Socket Set | | | |
| SC1832R | Spark Plug Socket 9/16" | 2-1/2" | 25/32" | • |
| SC2032R | Spark Plug Socket 5/8" | 2-1/2" | 27/32" | • |
| SC2632R | Spark Plug Socket 13/16" | 2-1/2" | 1-1/4" | • |
| SCD1832RD | Extra Deep Spark Plug Socket 9/16" | 5-7/8 | 25/32" | • |
| SCD2032RD | Extra Deep Spark Plug Socket 5/8" | 5-7/8 | 27/32" | • |
| SCD2632RD | Extra Deep Spark Plug Socket 13/16" | 5-7/8 | 1-1/4" | • |
| SCU1832R | Universal Spark Plug Socket 9/16" | 3-7/16 | 25/32" | • |
| SCU2032R | Universal Spark Plug Socket 5/8" | 3-7/16 | 27/32" | • |
| SCU2632R | Universal Spark Plug Socket 13/16" | 3-7/16 | 1-1/4" | • |

SPECIALITY TOOLS FUEL



MASTER DISCONNECT AND A/C FUEL LINE **DISCONNECT SETS**

| PRODUCT # | SIZE | DESCRIPTION | SI | ET |
|-----------|-----------------|--|----|----|
| MD4000 | Master Disconn | ect Set | | |
| DTS37000 | 6 Piece A/C Fue | el Line Disconnect Set | | |
| DS410 | 5/16" | Angled Disconnect - Yellow | | • |
| DS420 | 3/8" | Angled Disconnect - Blue | | • |
| LIS39430 | 1/2" | Angled Disconnect - Red | | • |
| LIS39440 | 5/8" | Angled Disconnect - Green | | • |
| LIS39450 | 3/4" | Angled Disconnect - Orange | | • |
| LIS39460 | 7/8" | Angled Disconnect - White | | • |
| LIS37010 | 7/8" | Disconnect Tool | • | • |
| LIS37020 | 3/4" | Disconnect Tool | • | • |
| LIS37030 | 5/8" | Disconnect Tool | • | • |
| LIS37040 | 1/2" | Disconnect Tool | • | • |
| L37050 | 3/8" | A/C Fuel Line Disconnect Tool | • | • |
| LIS37060 | 5/16" | Disconnect Tool | • | • |
| FF350 | | GM [®] Fuel Filter Disconnect | | • |
| LIS37500 | | GM [®] Fuel Module Disconnect | | • |
| MD4000-4 | | Right Arm GM® Fuel Module Disconnect | | • |
| MD4000-5 | | Right Arm GM [®] Fuel Module Disconnect | | • |
| MD4000-9 | 5/16"-3/8" | Scissor Disconnect | | • |
| TD960 | | Ford® Trans Oil Cooler Disconnect | | • |



HOSE PINCHING CLAMPS

- Lightweight, sturdy, non-conductive locking clamps for fuel, vacuum, and radiator hoses
- Both sets include small, medium, and large sizes
- which cover 7/64" to 2-1/4"

| PRODUCT # | DESCRIPTION | SIZE | SI | ET |
|-----------|---------------------|--------------|-----|----|
| FCSA | 3 Piece Angled Hose | Pinching Cla | mps | |
| FCS1 | 3 Piece Hose Pinchi | ng Clamps | | |
| FCSA1 | Fuel Line Clamp | Small | | ٠ |
| FCSA2 | Fuel Line Clamp | Medium | | ٠ |
| FCSA3 | Fuel Line Clamp | Large | | ٠ |
| FCS1A | Hose Clamp | Small | • | |
| FCS1B | Hose Clamp | Medium | • | |
| FCS1C | Hose Clamp | Large | • | |



2 PIECE HOSE PINCHER SET

- · A very quick and easy way to pinch off vacuum lines, fuel lines, and other small diameter lines without damage
- · Body is made from strong fibreglass reinforced nylon for long life and resistance to solvents

FLP1 **FUEL LINE PLIERS**

- Used to remove fuel lines with quick
- connect, snap/slide, and lock couplers · Adjustable jaws provide use in hard-to-
- reach areas with restricted access Suitable for use on multiple
- vehicle types

PHR900 2 PIECE WIDE TIP

HOSE REMOVER SET

- · Removes rubber hoses from fittings and clamps
- Wide, smooth tip design helps prevent punctures Short remover designed to push hoses off
- · Curve of the long remover is ideal for pulling hoses off

INCLUDES:

FUEL

- PHR9001* Short Wide Tip Hose Remover, 9" length
- PHR9002* Long Wide Tip Hose Remover, 12-1/4" length

*Available seperately.

FIT810B **BASIC FUEL INJECTION TEST KIT**

- · Includes adapters to service many domestic, Japanese,
- and marine applications Includes both GM[®] and Ford[®] test port fittings, in-line
- and end-of-line hose connections, and fuel bolt sizes 6mm-12mm
- · All adapters and gauge heads have quick disconnect fittings for ease of use



SPECIALITY TOOLS

S115KP **DIESEL INJECTOR PULLER®**

- · Pulls injectors on Detroit Diesel® and Cummins® engines
- · Bend and long handle provide extra leverage









PHR950 2 PIECE WIDE TIP LONG REACH HOSE REMOVER SET

- Long length ideal for removing hoses from hard-to-reach fittings and clamps
- Wide, smooth tip design helps prevent punctures
- Straight remover designed to push hoses off
- Curve of the hook remover is ideal for pulling hoses off

INCLUDES:

- **PHR9501*** Wide Tip Hose Remover, 25-3/4" length
- PHR9502* Long Wide Tip Hose Remover Hook, 25-3/4" length

*Available seperately.





EMISSIONS

OSW28F BENT-HANDLE FLEX-HEAD OXYGEN SENSOR WRENCH - 6-PT.

- Flexible head design assists in the removal of stubborn O₂ sensors that are 7/8" in diameter, a common size to most vehicles
- Pivots to allow more angles of placement

OSW-SET

mac Tools

11 PIECE OXYGEN SENSOR SOCKET SET

• Master oxygen sensor and sending unit tool set

| PRODUCT # | DESCRIPTION | APPLICATIONS | SIZE | SET |
|----------------|----------------------------------|---|-----------------------|-----|
| OSW-SET | 11 Piece Oxygen Sensor Socket Se | t | | |
| 0SW101 | Oxygen Sensor Socket | 0_2 and oil pressure sending units on late | 1/2" x 29mm x 90mm | • |
| 0SW102 | Oxygen Sensor Socket | 1980's / mid-1990's vehicles | 3/8" x 7/8" x 90mm | • |
| 0SW103 | Oxygen Sensor Socket | Vacuum switches with a 7/8" hex and some $\rm O_{2}$ sensors | 1/2" x 27mm x 85mm | • |
| 0SW104 | Oxygen Sensor Socket | Thermal sensor switches on 1973-1977 GM® vehicles | 3/8" x 7/8" x 80mm | • |
| OSW105A | Oil Sending Unit Socket | $\boldsymbol{0}_{_{2}}$ sensors and vacuum switches on many domestic and imported vehicles requiring wire clearance | 1/2" x 1-1/16" x 74mm | • |
| OSW106 | Oxygen Sensor Socket | Designed with a slot to accommodate the connectors on heated $0_{_{2}}$ sensors | 3/8" x 7/8" x 50mm | • |
| 0SW107 | Offset Oxygen Sensor Wrench | Low profile for use in tight areas | 3/8" x 7/8" x 30mm | • |
| OSW108 | Special Tube Socket | To remove $0_{\mathbf{z}}$ sensors on many European vehicles; also for Mercedes diesel injectors | 3/8" x 22mm | • |
| OSW109 | Offset Oxygen Sensor Wrench | Allows maximum accessibility when removing $\rm O_2$ sensor sockets; also for Super-Duty 12- and 6-PT. applications | 2-1/8" | • |
| 0SW110 | Deep Oxygen Sensor Socket | Side slot allows wire clearance | 3/8" x 3-7/8" | • |
| 0SW111 | Oxygen Sensor Thread Chaser | Can be used to clean and repair threads on exhaust 0_2 sensor parts; also to clean threads on M18 x 1.5 spark plug socket | _ | • |

SC1531A OXYGEN SENSOR SOCKET

- Remove and install oxygen sensors on computerized engine control vehicles
- Can be used in conjunction
 with a torque wrench
- Size: 7/8" x 3-7/8"

| TOOLS AND NOTES | ENGINE SIZE | CONFIGURATION | REPRESENTATIVE CAR MODEL |
|---|-------------|---------------|------------------------------------|
| SC1531A | 1.9L | 1-4 | Escort [®] GT |
| SC1531A (LOTS OF ROOM, SMALL SENSOR) | 2.3L OHC | 1-4, FBC | Mustang® / Capri® |
| SC1531A (HS) | 2.9L | V-6, EFI | Ranger® |
| SC1531A OR WRENCH (HS) | 2.9L | V-6 | Bronco II® |
| SC1531A OR WRENCH (LOTS OF ROOM, HS) | 3.0L | E-6, EFI | Aerostar® |
| SC1531A (CLOSE TO WALL, DIFFICULT TO FIT) | 3.8L | E-6, EFI | Cougar® / T-Bird® LTD/ Marquis® |
| SC1531A (MOVE 1/4" TUBE TO FIT) | 4.9L | 16 | F150® |
| SC1531A (HS) | 5.0L | V-8, EFI | Marquis Grand F150® |

MAL

* Does not list all possible models. EFI - electronic fuel injection, FBC - feedback carburetor, NHS - non-heated $O_{\rm 2}$ sensor, HS - heated $O_{\rm 2}$ sensor.



OSW8875B Oxygen Sensor Wrench

- Compact design
- Made from quality heat-treated steel, this tool works on both foreign and domestic cars
- Drive size: 3/8"

SPECIALITY TOOLS TESTING





TPT460M TRANSMISSION / OIL PRESSURE TEST KIT

- This professional kit can be used for domestic and import applications
 High and low pressure gauges make this kit useful for both transmission
- High and low pressure gauges make this kit useful for both transmission and engine work
- Comes complete with adapters for most applications and is designed to be used for either static or road testing

INCLUDES:

- M8 x 1.0 to 1/8" NPT
- M10 x 1.0 to 1/8" NPT
- M12 x 1.75 to 1/8" NPT, 1/8" NPT x 2" Male
- 1/6 NFT X 2 Mail
 1/4" NPT Male x
- 1/8" NPT Male
- 1/8" NPT Female
 1/4" NPT Male / Female,
- 3/8" NPT Male x 1/8" Female
- 1/8" NPT Male x 1/8" Female
 1/16"-27 NPT Male x 1/8"-27
- 1/10 -2/ INPT Male X 1/8"-2

326



CT155A Deluxe compression test kit

- · Complete with standard and speciality adapters
- This deluxe kit offers a complete package for compression testing on gasoline engines
- Kit includes the deep well connector used on recessed plug well style heads and the Ford[®] Triton[™] engine adapter using 16mm thread plugs

INCLUDES:

- 14mm Deep Well Extension
- 12mm Adapter
- 16mm Compression Tester Adapter
- 18mm Adapter



CLD210MA DIFFERENTIAL CYLINDER PRESSURE TESTER

- Quickly locates internal engine problems such as bad rings, valves, and leaking head gaskets
- Comes with adapters for most applications

INCLUDES:

- 10mm Adapters
- 12mm Adapters
- 18mm Adapters
- · Blow-Moulded Case



VP5000K

AUTOMOTIVE PRESSURE TEST KIT

- · Can be used as a complete one-person brake bleeding kit with 12-oz. bottle and rigid quick connect to pump
- Dual hand pump can produce and measure vacuum or pressure with equal performance and precision
- · Switches between vacuum/pressure at the turn of a switch ergonomically designed handle for ease of operation
- Single-hand vacuum/pressure release action allows multiple tests without disconnection
- Accessories to perform multiple vacuum and pressure tests on vehicle



CT900D DIESEL COMPRESSION TESTER SET

- Includes 0 to 1,000 PSI (0-70 bars) compression gauge and adapters for GM®, VW®, Small Cummins®, Mercedes Benz®, plus adapter to fit Bacharach fittings
- Release valve allows for venting resets for repeat tests
- Swivel end connector attaches to adapters
- · Records maximum pressure
- · High-pressure hose, 16-1/2" long

| PRODUCT # | APPLICATIONS | SIZE | SET |
|-----------|--|----------------------------------|-----|
| CT900D | Diesel Compression Tester Set in Metal Box | | |
| CT700D | Compression Tester | - | • |
| SGT34730 | GM [®] and Ford [®] / International 6.9L | Fits Glow Plug Port | • |
| CT740VW | Volkswagen® | Fits Fuel Injector Port | • |
| SGT34760 | Small Cummins® | Fits into Nozzle / Injector Port | ٠ |
| CT780MB | Mercedes Benz® | Fits Glow Plug Port | • |
| SGT34770 | Heavy-Duty Equipment / Heavy-Duty Injector Port | Fits Bacharach Adapters | ٠ |



LATINAL.

SPECIALITY TOOLS TESTING

DDRG6059F

DIGITAL CALIPER 0 - 2.25

- · Three keys: mm/in
- (metric/inch conversion) · ABS (absolute and relative
- measurement conversion)
- ON-ZERO (power on/off and zero setting)
- · Hardened stainless steel construction. thumb wheel and lock screw, automatic
- power off and RS232 output
- Supplied with one spare battery
- Meets DIN862 specification
- · Blow-moulded case

DDRG465

DIGITAL ROTOR / BALL JOINT DIAL INDICATOR

- RS232 output
- Spare battery
- · Checks ball joint wear
- and disc rotor run-out
- · Indicator mounted on flex-arm Meets DIN878 specification
- Blow-moulded case





FG030

25-BLADE METRIC

MASTER GAUGE

FG013 22-BLADE MASTER GO-NO-GO GAUGE

FG15

INCLUDES:

| PRODUCT # | BEND | BLADE SIZE | BLADE SIZE MM | |
|-----------|------|---------------|---------------|---|
| FG002 | 0° | 3" x 1/2" | 76.2 x 12.7 | .0015, .002, .003, .004, .005, .006, .007, |
| FG013 | 0° | 3" x 1/2" | 76.2 x 12.7 | .004006, .005007, .006008, .00 .016018, .017019, .01 |
| FG015 | 0° | 1-3/4" x 1/4" | 44.5 x 6.4 | .011, .012, .013 |
| FG030 | 0° | 3" x 1/2" | 76.2 x 12.7 | .04, .05, .06, .07, .08, .09 |
| FG15 | 45° | 6" x 1/2" | 152.4 x 12.7 | 007009, .008010, .009011, .010012 |





MP500A STETHOSCOPE

- Unique sound chamber and super-thin diaphragm greatly amplifies sounds
- · Pinpoints source of noises in engines, transmissions, differentials, and bearings
- Longer probe can reach deep into engine compartment

DDI350 DIGITAL DIAL INDICATOR WITH MAGNET

- RS232 output
- Spare battery
- · Measures distance, checks alignment, roundness and run-out, cam shaft, and valve guide wear
- · Powerful magnetic base
- Meets DIN878 specification
- Blow-moulded case





FG015 **16-BLADE MASTER IGNITION GAUGE**



For valve adjustment

• 15 x Step-ground • 15 x Go-No-Go blades

BLADE THICKNESS MM .008, .009, .010, .011, .012, .013, .014, .015, .016, .018, .020, .022, .024, .025, .028, .030, .032, .035 07-009.008-010.009-011.010-012.011-013.012-014.013-015.014-016.015-017.018-020.019-021.020.022.021.023.022-024.025.024-026.025-027 13, .014, .015, .016, .017, .018, .019, .020, .022, .024, .025, .028, .030, .032 9, .10, .15, .20, .25, .30, .35, .40, .45, .50, .55, .60, .65, .70, .75, .80, .85, .90, .95, 1.00 12, .011-.013, .012-.014, .013-.015, .014-.016, .015-.017, .016-.018, .017-.019, .018-.020, .019-.021, .020-.022, .023-.025, .025-.027, .026-.028, .028-.030

329

SPECIALITY TOOLS PULLERS



PJ200SB 2-TON 2-/3-JAW PULLER · Reversible jaws grip tighter

as more pressure is applied · Convertible design allows tool to be used in 2- or 3-jaw mode



PBP1170C PILOT BEARING PULLER

 Built specially for inside pulling jobs, and particularly for removing flywheel pilot bearings on autos, trucks, and tractors · Also practical for pulling motor, generator, and magnet bearings .

PP955B

PULLER

PILOT BEARING



THE PJ200SB PULLER SET MAY BE ASSEMBLED INTO THE FIGHT DIFFERENT CONFIGURATIONS AS SHOWN

| PRODUCT # | DESCRIPTION | CAPACITY Tons | REACH In. / Mm | SCREW SIZE | SPREAD In. / Mm |
|-----------|----------------------|------------------|-------------------|--------------------|--------------------|
| PJ200SB | Eight-Way Puller Set | 2 | 3-3/8" / 85.7 | 3/8" - 24 x 4-7/8" | 4-3/4" / 120.7 |

RATCHETING GEAR PULLER

- · Quick-release jaws for fast changes between two- and three-jaw mode • Ratcheting design holds jaws
- in position while setting puller
- Jaws are reversible for pulling on the inside or outside of object needing pulled

| PRODUCT # | DESCRIPTION | CAPACITY [TONS] |
|-----------|----------------|-----------------|
| GP102 | 2-3 Jaw Puller | 2 |
| GP105 | 2-3 Jaw Puller | 5 |
| GP107 | 2-3 Jaw Puller | 7 |

PS16LP-SET **16 PIECE SLIDE HAMMER** & PULLER SET

- · Removes bushings, bearing races, and pressed-in-studs
- Autobody dent puller attachments: 2 lb. slide hammer, 3-8/16" threaded slide screw, inside spread from 3/8" to 1-1/4", outside spread from 0" to 3", and a maximum reach of 2-1/2"

INCLUDES:

· Autobody dent puller attachments: 2 lb. slide hammer, 3-8/16" threaded slide screw, insode spread from 3/8" to 1-1/4", outside spread from 0" to 3", and a maximum reach of 2-1/2"



BH581B BLIND HOLE BEARING PULLER SET

• For pulling jobs requiring an internal pull • Four collet sizes: 7/16" to 1/2", 9/16" to 11/16", 5/8" to 1", 1" to 1-1/4", for a wide range of applications

INCLUDES:

- 2-1/2-lbs. Slide hammer with T-handle
- Blow-Moulded Case



PS959B

SLAMMER HAMMER EIGHT-WAY PULLER

• 5 lbs. Slide hammer

| INSIDE SPREAD | OUTSIDE SPREAD | SLIDE ROD SIZE |
|---|-------------------------------------|----------------|
| 1-1/4" to 4-1/4" (31.8mm to 108.0mm) | 1" to 4-1/2" (25.4mm to 114.3mm) | 5/8"-18" x 23" |



TOOLS





PB518B **5-TON BAR-TYPE PULLER / BEARING SEPARATOR SET**

• Two bearing splitters (2" and 3"), four sets of hex push-puller legs and bar-type puller head

• 5" Puller cross-bar with 6-1/4" forcing screw

PB518B-4 **FORCING SCREW**



PS1190B SLAMMER HAMMER PULL SET

- Deluxe version of the popular Slammer Hammer
- This set will make up to ten different pullers
- · Includes a wider assortment of jaw sizes, a front hub puller assembly, and a forcing screw and sleeve



SPECIALITY TOOLS EQUIPMENT



PP522B LARGE GEAR AND **PULLEY PULLER**

- Removes parts with tapped holes such as gears and pulleys • Any cap screws up to 1/2" diameter
- can be used (not included)



WW676A WINDSHIELD WIPER **ARM PULLER**

- Removes wiper arms on many foreign and domestic cars and light trucks Prevents damage to wiper arm
- or hood cowling during removal

| PRODUCT # | PULLER BLOCK WIDTH IN. / MM | SCREW | SPREAD RANGE IN. / MM |
|-----------|-----------------------------|-------------------|------------------------------|
| PP522B | 8-1/4" / 209.6 | 3/4"-16 x 11-5/8" | 2" to 7-3/4" / 50.8 to 196.9 |


PP7208C **FRONT HUB PULLER**

- · Removes and installs front hubs on today's FWD cars
- · Creates up to five tons of working force. for use on most front wheel drive cars, plus a spare locknut that allows the use of a standard slide hammer puller for rear axle flanges
- With locknut for rear axle flanges



- Fits most passenger cars and light trucks for removal of flange-type rear axles • 5-lbs. Slide hammer with pulling plate, services axles with bolts or studs up to 9/16" diameter
- Fits 4, 5, or 6 bolt stud circle to 5-9/16" (141.3mm)





STP600B **43 PIECE DELUXE MASTER BOLT GRIP SET**

- · Covers almost every car, pickup, SUV and small engine
- Capable of handling almost every 2- or 3-way bolt pull possible
- · For use on a variety of jobs: harmonic balancers, steering wheels, crankshaft pulleys, and gears

INCLUDES:

- 1 x 3/4" Centre x 4-1/4" Diameter Heavy-Duty 4-Way Slotted Puller Yoke
- 1 x 3/4-16UNF x 5-3/8" Grade 5 Hardened Live-Centre Forcing Screw
- 1 x 3/4-16UNF x 2-3/4" Grade 5
- Hardened Live-Centre Forcing Screw • 3 x 5/16-24 UNF x 3" Grade 8
- Special Stepped Bolts 1990 and Newer GM® 3300-3800
- V-6 Crankshaft Pulleys
- 1 x Blow-Moulded Case
- 1 x Detailed Application Chart



- 3 x 8mm x 1.25 x 90mm • 3 x 8mm x 1.25 x 45mm
- 3 x 8mm x 1.25 x 65mm • 3 x 10mm x 1.5 x 35mm Grade 8 Washer Head Bolts



MAL

MV6400MAC FLUID DISPENSING SYSTEM

- The MV6400MAC is designed for topping-off fluid reservoirs including master cylinders, gear boxes, transmissions, power steering reservoirs, etc.
- · Its convenient size and 5' long hose with dispensing wand and flow control valve make it ideal for accessing hard-to-reach reservoirs and fill plugs
- · For transmission refill and pressure bleeding applications, the MV6400MAC is compatible with a wide selection of ATF and pressure bleed adapters



MV7201A **8.8 LITRE FLUID EVACUATOR / DISPENSER**

- · Creates vacuum and pressure · Can evacuate and dispense
- most automotive liquids
- · Larger capacity 8.8 litre fluid reservoir
- Automatic flow control valve
- prevents overfilling · No electric or compressed air required
- · Can be used with our MV7205A
- brake bleeder kit

BB2500

- for extracting and pressure for dispensing • Includes accessories for extracting used brake fluid while refilling with new
- · Used or new fluids are dispensed by switching from vacuum to pressure
- Isolated flow control and pressure / vacuum switch valves provide simple functionality control · Redundant pressure control systems
- safely maintain peak output pressure below 30 psi (2 bar)
- INCLUDES:
- 1 x Pneumatic lid for evacuation
- and dispensing • 1 x 2.5L bottle
- 1 x Fluid Evacuation W

- FE8000 **7.3 LITRE FLUID EVACUATOR** · Evacuate most automotive liquids and chemicals
- Automatic flow control
- prevents overfilling
- · Pressure relief valve for safety
- · Fully sealed cylinder
- Durable polyethylene construction
- Dipstick tubes for engine oil removal
- · Pour spout for easy dispensing of fluids
- · No power required

332





BLEEDER AND FLUID DISPENSER

· Compressed-air-powered system designed for performing one-person vacuum brake and clutch bleeding · Utilizes compressed "shop-air" to produce vacuum

- · 2.5-quart (2.5-litre) capacity reservoir

MV7300-MAC **PNUEMATIC AIR OPERATED** FLUID EVACUATOR





MV6412MAC 2.5-GAL ATF REFILL SYSTEM

- The MV6412MAC combines the new Fluid Dispenser with our popular ATF refill adapter kit to provide a complete system for servicing today's sealed automatic transmissions
- The dispenser allows the operator to fill or top-off transmissions with up to 2.5-gallon of fluid between refills, while the pressurized operation frees the operator from continual pumping



PBT71201 **TRANSMISSION ADAPTER KIT**

- Kit contains 10 pressure hose adapters to use with PBT71196 Drill Pump to efficiently refill sealed automatic transmissions
- Quick-connect fittings on adapters and pressure hose for easy interchange
- · Included pressure hose with quick-couple fittings for quick adaptor interchange
- Adapters made from lightweight, high strength composite material with high chemical resistance
- High-impact resistance prevents damage to adapter thread if dropped

INCLUDES:

- Adapter M22 x 1.5mm: VW[®] / Audi[®] with CVT Transmission
- Adapter M24 x 1.5mm: VW[®] / Audi[®] with DSG Transmission
- Adapter M30 x 1.5mmm: VW®
- Adapter M8 x 1.0mm x 46mm: VW [®] Tiguan
- Adapter M18 x 1.5mm with flex hose: Toyota® ATF
- Adapter 5/16 24 UNF x 46mm: Volvo® ATF
- Adapter M10 x 1.0mm x 95mm; VW[®] ATF
- Adapter M12 x 1.5mm x 83mm: Mercedes-Benz[®] with 722.9 7G Tronic Transmission
- Adapter 45° x 142mm: General • Adapter - 1/8" NPT x 118mm: Ford® ATF
- Pressure Hose: All



BT500A

COMBUSTION LEAK TESTER KIT BT700A **BLOCK TEST FLUID**

BTD600

COMBUSTION LEAK FLUID FOR DIESEL ENGINES

- · Quickly detects the presence
- of combustion gases in the radiator
- Indicate combustion leaks when
- Vacuum Hose the fluid turns from blue to yellow 16-oz. Bottle of Test Fluid

INCLUDES:

Block Tester



SPECIALITY TOOLS EQUIPMENT

PBT80020

QUICKDIAL 2-WAY DIAGNOSTIC PUMP

- · 2-Way pressure and vacuum test functions · Intuitive rotary dial mode switch
- · Pistol grip with lever
- High volume efficiency in both pressure and vacuum mode
- · Manufactured from fiber reinforced composite materials
- Very high strength
- High impact resistance
- · Excellent chemical resistance
- Integrated rear mount gauge
- Optimum viewing angle

- Maximum impact protection High-quality silicon material hoses with quick couple hose fittings · Quick hose interchange
- No leaks under vacuum or pressure
- Custom blow mold storage case
- Maximum pressure: 30psi
- · Maximum vacuum: 28 in Hg Stroke volume: 1 cubic inch (16cc)
 - · Pump weight: 20.1 ounce

- · Bleed fuel systems fast
- · Bleed diesel fuel systems quickly and easily after filter replacement
- Pump and operate vacuum mode to easily
- · Use to bleed brake systems, bleed fuel systems after filter replacement and
- · Overfill protection Fitted with overfill
- · Lightweight and high chemical resistant manufacture from high strength composite
- Handsfree operation features a hanging hook to conveniently operate pump and

- **MT770A TAILPIPE AND**

EXHAUST CUTOFF 19mm diameter cutting

- · Cuts thick and thin walled pipe from 3/4" to 3-1/4"
- 1/4 turn for complete cut



334



Specifically designed for differential and transmission service

- · Converts either your 3/8" drive air ratchet or cordless drill into a fluid transfer pump
- Quick-couple fittings allow easy hose changes and no-drip storage Blow-moulded case for
- convenient storage

PBT71196

- PBT80021 FLUID COLLECTION CONTAINER
- · Connect to the PBT80020 QuickDial 2-Way
- transfer fluids
- evacuate power steering systems
- shut-off valve
- materials
- move the suction hose
- Maximum vacuum: 28 in. Hg
- · Container volume: 500ml
- wheels on every pivot
- (19mm to 83mm) in diameter



TPS344 EXHAUST AND **TAILPIPE STRETCHER**

- Stretches all types of exhaust pipes including stainless steel
- Use with impact wrench to guickly stretch pipes for connection
- Two collet sets fit pipes from 1-5/8" to 2-7/16"
- · Can be used on the car

C38350 **EXHAUST PIPE** HANGER PLIERS

 Separates exhaust hanger brackets from rubber supports

STEERING & SUSPENSION **BALL JOINT TOOLS**

STEERING & SUSPENSION TIE ROD TOOLS



UJP904 AUTOMOTIVE U-JOINT PULLER

- For disassembling seized U-joints in minutes on many cars, light-duty trucks and farm machinery
- · Eliminates vise-and-socket or hammering methods
- · Reduces risk of damage to the driveshaft,
- yokes, joints or bearing cups
- For U-joints with bearing cups 1" to 1.25" outside diameter

HCP650A **REMOTE-ACCESS HOSE CLAMP PLIERS**

- · Locking feature frees hand
- · Extra long reach for removal and installation of hard-to-reach hose clamps
- Fits hose clamps from 11/16" to 2-1/2"
- (18mm to 54mm) Precision-machined clamp at the end reaches where other pliers can't





UJP907

INTERMEDIATE U-JOINT PULLER

- Heavy-duty solution for disassembling U-joints, including many which are seized and stubborn, in minutes on many Class 7 and 8 trucks and machinery
- · Engineered for use with up to a 1" impact tool
- · Alternative to vice and socket, or hammering removal methods · Helps to prevent damage to the driveshaft, yokes, joints,
- or bearing cups
- One-piece unit without bolts, cables, or assembly required



· Allows for the removal and installation of press-fit ball joints on many GM[®] and Ford[®] light-duty trucks, vans, and SUVs through 2003; Dodge[®] light trucks through 1998; Dodge[®] vans, Durango, and Dakota through 2003; and Honda[®] Accord, Civic, del Sol, and Prelude through 2001

BJ7025MA BALL JOINT / U-JOINT PRESS

• Removes and installs pressed-in ball joints and U-joints

INCLUDES:

- 1 x Receiver Tube: 3" 0.D. x 2-3/4" I.D.
- 1 x Receiver Tube: 2-1/2" 0.D. x 2-1/4" I.D.
- 1 x Receiver Tube: 2" 0.D. x 1-3/4" I.D.
- 1 x C-Frame
- 2 x Adapter Plates
- 1 x Blow-Moulded Case





HCPR1 **REMOTE ACCESS HOSE CLAMP PLIERS**

- Unique jaw design fits all typical automotive clamps up to 2" (50mm)
- Ratchet lock with slide guide Bi-material grips with cable snap feature extra-heavy duty 5/64" (2mm) cable
- · Hose Clamp Pliers with flexible cable for remote access
- Works on the widest range of hose clamps



3 PIECE MOBEA HOSE CLAMP LOCK TOOL SET

 Designed to help technicians save time when removing and servicing engine hoses that are fastened with spring style clamps • There are three sizes of clamp locks included in this kit. covering the range of hose clamps used on most engines • No need to either unload a clamp, which can be difficult to reload. or leave pliers locked in place for the duration of the job Allows technicians to keep the clamp loaded, freeing up pliers for the next clamp



KC18A **HOSE CLAMP PLIERS**

- · For applying and removing spring clamps
- Recess in jaws grips spring
- Eliminates slip or twist

11





TR899 MULTI-PURPOSE RACK WRENCH

- · Services hex drive rack ends and round rack ends with either two or no flats
- · Suits multiple rack ends and sizes
- Use on vehicles with limited access to avoid need to remove rack assembly
- Prevents damage to rack components
- · Clamp force increases as load is applied



PARP9 **LOCKING PARROT PLIERS - 9"**

- Unique shaped jaws allow pliers to grasp a multitude
- of objects, regardless of shape · Ideal for standard fasteners, suspension components,
- tie rods, and rounded off bolts

TR6275A

TIE ROD / PITMAN ARM ADJUSTING TOOL SET

- For compact or full size cars and light trucks
- Permits 360° rotation of adjusting sleeve
- · Leverage easily applied by 1/2" ratchet or breaker bar

| PRODUCT # | DESCRIPTION | SLEEVE DIAMETER | APPLICATION | SET |
|-----------|--|--------------------|-----------------------------------|-----|
| TR6275A | Tie Rod / Pitman Arm Adjusting Tool Se | t | | |
| FT-86A | Tie Rod/Pitman Arm Adjusting Tool | 3/4" | Compact Cars | • |
| FT-86B | Tie Rod/Pitman Arm Adjusting Tool | 7/8" | Full Size Cars | • |
| FT-86C | Tie Rod/Pitman Arm Adjusting Tool | 1-1/8" | Light Trucks | • |
| FT-86D | Tie Rod/Pitman Arm Adjusting Tool | 1-7/16" | Ford® 3/4-Ton | • |
| FT-86E | Tie Rod/Pitman Arm Adjusting Tool | 1-13/16" | Ford® 3/4-Ton and 1-Ton Trucks | • |

PFK4150A

5 PIECE STEPPED PICKLE FORK KIT

ALIGNMENT TOOLS

- · Ideal kit for separating ball joints, steering dampeners, tie rods, Pitman arms, and other heavy-duty chassis and suspensions
- · Stepped fork design greatly reduces bounce back during heavy use
- Complete set includes three stepped forks and two handles: one for hammering and one for use in an air hammer (.401" shank)
- · Heavy-duty steel alloy forks withstand abuse and can be sharpened over the life of the tool





PSPKITA POWER STEERING PUMP PULLEY REMOVE AND INSTALL SET

- Remove and install a wide range of pulleys on Ford[®], GM[®], VW[®], and Chrysler[®] vehicles with Saginaw, Thompson, and Ford® C111 and C2 power steering
- · Includes adapters and spacers to install pulleys exactly to the right depth, from old Chrysler® alternators, to the latest models in all brands









MS629A MACPHERSON STRUT SPRING COMPRESSOR

· Centre screw uses ACME threads for strength and ease of operation



NOTES



HEAVY-DUTY SINGLE SHOT AIR GREASE GUN

- Heavy-duty composite body
- Comfortable cushion-grip
- 3-Way loading (bulk, 14-oz. cartridge, filler pump)
- · Bleeder valve for purging unwanted air
- 2 ml Output per stroke
- 3600 psi Output pressure
- 40:1 Ratio

GG33HD

GREASE GUN

HEAVY-DUTY PISTOL-GRIP

· Heavy-duty flexible 18" nylon hose

and 6" metal spout for easy use

seamless barrel to avoid dents

• Heavy-duty 1.7mm thick

 Aluminium head reduces the weight for easier use

• 16-oz. Bulk fill - 14-oz. Standard cartridge • 3-Way filling (bulk, cartridge, filler pump)



• Heavy-duty cast aluminium body

- for durability and long life
- Cushion-grip for comfort
- 3-Way loading (Bulk, 14-oz. cartridge, or filler pump)
- 288 ml/min of Output per stroke
- 3600 psi Output pressure
- 40:1 Ratio

GS19HD **HEAVY-DUTY SUCTION GUN**

- Heavy-duty 1.7mm thick seamless barrel with textured finish
- 12" Clear flexible tube
- Heavy-duty T-handle with finger grooves for easy use
- · Capacity: 16-oz.

GG43HD

HEAVY-DUTY LEVER GREASE GUN

- 16-oz. Bulk fill 14-oz. Cartridge
- 3-Way filling (bulk, cartridge, filler pump)
- Heavy-duty 1.7mm thick seamless barrel with textured finish
 - ACME threads machined in barrel for better seal
- · Aluminium head reduces the weight for easier use
- · Cushioned lever for comfort · Heavy-duty T-handle with finger grooves for easy use

INCLUDES:

• Heavy-Duty Flexible 12" Nylon Hose • 6" Metal Spout



· All adapters utilize quick couplers

Blow-moulded case

| PRODUCT # | DESCRIPTION | SET |
|---------------|---|-----|
| GGA8B | 8 Piece Grease Adapter Set | |
| GGA810 | Hypodermic Needle Coupler | • |
| GGA820 | Seal-Off Dispenser | • |
| GGA830 | Narrow Needle-Nose Dispenser | • |
| GGA840 | 3" Straight Needlepoint Coupler | • |
| GGA850 | Needlepoint Coupler Right Angle | • |
| GGA860 | Right Angle Tight Tolerance Coupler | • |
| GGA870 | Grease Coupler | • |
| GGA880 | 16" Rubber Grease Hose with Spring Guard and 4-Jaw Coupler | • |





11 341